# **PRO-C**<sup>™</sup>

Simple programming and flexible station expansion make Pro-C the professional's choice for residential and light commercial systems.

### **KEY BENEFITS**

- Number of stations:
  - Modular Pro-C capacity from 4 to 16
    Fixed PCC with 6- and 12-station options
- 3 independent irrigation programs (4 start times each) allow for customised scheduling
- 6-hour maximum station run time provides flexibility for differing application amounts
- 1 sensor input available for use with Solar Sync™ or any Clik sensors
- 1 P/MV output for pump start relay and master valve activation
- Dedicated Solar Sync dial position provides logic for smart water savings
- Easy Retrieve<sup>™</sup> memory allows for manual backup and retrieval of preferred settings and programming
- QuickCheck™ provides simple diagnostics of faulty field wiring

### **OPERATING SPECIFICATIONS**

- Transformer input: 120 VAC or 230 VAC
- Transformer output (24 VAC): 1 A
- Station output (24 VAC): 0.56 A
- P/MV output (24 VAC): 0.28 A
- Approvals: UL, cUL, FCC, CE, RCM
- Warranty period: 2 years




**Plastic Indoor** Height: 22.9 cm Width: 25.4 cm Depth: 11.4 cm



**Plastic Outdoor** Height: 22.9 cm Width: 25.4 cm Depth: 11.4 cm

## Compatible with:





Smart WaterMark

Recognised as a responsible water-saving tool when used with a Solar Sync sensor  $% \left( {{{\rm{S}}_{{\rm{S}}}}} \right)$ 

# STANDARD CONTROLLERS

### **PRO-C - SPECIFICATION BUILDER:** ORDER 1 + 2 + 3 + 4 Model 2 Transformer 3 Indoor/Outdoor 4 Options PC-4 = 4-station base **00** = 120 VAC (blank) = Outdoor model (blank) = No option module controller (internal transformer) i = Indoor model **E** = 230 VAC with PCC-6 = 6-station 01 = 230 VAC (plug-in transformer) European connections PCC-12 = 12-station **A** = 230 VAC with Australian connections (outdoor models have internal transformer with cord)

### Examples:

**PC-400** = Modular 4-station outdoor base unit, internal 120 VAC transformer, and plastic cabinet **PCC-601i-E** = Fixed 6-station indoor controller, plug-in 230 VAC transformer with European connections, and plastic cabinet

PCC-1200 = Fixed 12-station outdoor controller, internal 120 VAC transformer, and plastic cabinet

PC-SERIES STATION EXPANSION	
Modules	Description
PCM-300	3-station plug-in module
PCM-900	9-station plug-in module (maximum, one per controller)