



Aircol MR

Rotary Screw Compressor Lubricant

Description

The Castrol Aircol™ MR compressor oil range of premium lubricants are formulated from highly refined mineral oils and novel additive technology to give outstanding antiwear and antirust performance to meet the requirements of Atlas Copco and similar types of compressor design.

Application

Aircol MR incorporates a carefully balanced antioxidant system providing improved oxidative and thermal stability giving “extended” service life for both oil flooded and oil injected rotary screw compressors operating continuously at air discharge temperatures up to 90°C. The product has been designed to meet service drain intervals of 4000 hours. For intermittent or continuous operation with air discharge temperatures above 90°C the manufacturers’ standard oil change periods should be used.

The Aircol MR range is fully compatible with nitrile, silicone and fluoropolymer seal materials.

Aircol MR is classified as follows:

- ISO 6743-3 Compressor Oils
- DAG and DAH for rotary air compressors

Aircol MR grades meet the requirements of:

- Atlas Copco for 4000 hour oil life.

Advantages

- Very low deposit forming tendencies extends oil change intervals and air filter life which contributes to a reduction in maintenance costs.
- Good air/oil separation properties at the separator element reduces risk of oil carry over.
- Good antiwear protection reduces rotor wear.
- Excellent water separation characteristics allows condensation to readily separate from the oil, minimising the risk of emulsions which could block the oil separator element.
- Excellent oxidation and thermal stability minimises oil thickening and extends the oil separator life and reduces fouling of coolers & pipes.
- Prevents corrosion when operating under humid conditions.

Typical Characteristics

Name	Method	Units	MR 32	MR 46	MR 68
Appearance	Visual	-	Clear & Bright	Clear & Bright	Clear & Bright
ISO ViscosityGrade	-	-	32	46	68
Density @ 15°C	ISO 12185/ ASTM D4052	g/ml	0.87	0.88	0.88
Viscosity, Kinematic 40°C	ISO 3104/ ASTM D445	mm ² /s	32	46	68
Viscosity, Kinematic 100°C	ISO 3104/ ASTM D445	mm ² /s	5.6	6.7	8.6
Viscosity Index	ISO 2909/ ASTM D2270	None	110	100	100
Foam Sequence I, Tendency/Stability	ISO 6247/ ASTM D892	ml	30	30	30
Pour Point	ISO 3016/ ASTM D97	°C	-21	-21	-21
Flash Point, PMCC	ISO 2719/ ASTM D93	°C	216	222	222
Rust Test, Procedure B	ISO 7210/ ASTM D665B	-	Pass	Pass	Pass
Demulsification 54°C, mins to 40/37/3	ISO 6614/ ASTM D1401	minutes	15	15	15
RPVOT (Rotating bomb)	ASTM D2272	minutes	700	700	700

Subject to usual manufacturing tolerances.

Aircol MR
21 Dec 2010
Castrol, the Castrol logo and related marks are trademarks of Castrol Limited, used under licence.

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Material Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. No responsibility is taken by either BP plc or its subsidiaries for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale. You should consult our local representative if you require any further information.

Castrol Industrial, Technology Centre , Whitchurch Hill , Pangbourne , Reading , RG8 7QR , United Kingdom

www.castrol.com/industrial