



MEDITRAN E 40

Meditran E 40 is a heavy duty diesel oil, formulated from high viscosity index base oil and balanced additive system.

***Meditran E 40** adalah pelumas mesin diesel tugas berat, yang diformulasikan dari base oil yang mempunyai viscosity index tinggi dan aditif yang seimbang.*

TYPICAL CHARACTERISTICS		
Characteristics	Test Method	MEDITRAN E 40
SAE Viscosity Grade		40
Total Base Number, mg KOH/g	ASTM D - 2896	10.90
Density at 15 °C, Kg/L	ASTM D - 4052	0.8939
Kinematic Viscosity at 40 °C, cS	ASTM D - 445	129.7
at 100 °C, cSt	ASTM D - 445	13.52
Viscosity Index	ASTM D - 2270	99
ASTM Colour	ASTM D - 1500	L 3.5
Flash Point (COC), °C	ASTM D - 92	246
Pour Point, °C	ASTM D - 5950	-9

PERFORMANCE LEVELS

Meditran E 40 meets the performance level of API CF.

TINGKATAN MUTU

Meditran E 40 memenuhi tingkatan mutu API CF.

APPLICATIONS

Meditran E 40 is suitable for lubrication of heavy or moderate duty diesel engine, whether its turbocharged, supercharged, or naturally aspirated.

PENGUNAAN

Meditran E 40 digunakan untuk pelumasan mesin diesel tugas berat dan medium jenis turbocharged, supercharged, atau naturally aspirated.