



## Aircol SW Range

Synthetic refrigeration compressor lubricant

### Description

The Castrol Aircol™ SW range of synthetic refrigeration lubricants are formulated from polyolester base stocks.

### Application

They are specifically designed for use with refrigeration systems using environmentally friendly HFC refrigerants, in particular R134a.

### Advantages

The synthetic base stocks used in the Aircol SW range are fully miscible with HFCs, in particular R134a, even at temperatures well below the minimum likely to be encountered in service.

The Aircol SW grades have been formulated to enhance hydrolytic stability, load carrying and inhibition against copper plating. They are wax free and hence have very low pour points. This ensures the evaporator remains clean (consequent efficient heat transfer) and reduces the risk of pipe blockages.

### Typical Characteristics

Name	Method	Units	SW 46	SW 68
Density @ 20°C	ISO 12185 / ASTM D4052	kg/m <sup>3</sup>	977	977
Base Oil Viscosity @ 40°C	ISO 3104 / ASTM D445	mm <sup>2</sup> /s	46	68
Base Oil Viscosity @ 100°C	ISO 3104 / ASTM D445	mm <sup>2</sup> /s	7.1	9.4
Pour Point	ISO 3016 / ASTM D97	°C	-46	-39
Flash Point - closed cup method	ISO 2719 / ASTM D93	°C	260	270

Subject to usual manufacturing tolerances.

Aircol SW Range  
04 Aug 2016  
Castrol, the Castrol logo and related marks are trademarks of Castrol Limited, used under licence.

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, to the extent that it is permissible by law to exclude warranties and representations, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Material Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. Refer to the MSDS, available from our website for further information. No responsibility is taken by either Castrol NZ, BP plc or its subsidiaries for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale. You should consult our local representative if you require any further information.

Castrol NZ (a business division of BP Oil New Zealand Limited)  
Technical Advice Line: 0800 10 40 60 / Customer Service: 0800 CASTROL (227 876)  
<http://msdspd.castrol.com>