



MESRAN MARINE 2T SAE 20

MESRAN MARINE 2T SAE 20 is a lubricating oil for two stroke gasoline engine with water cooling system. This oil is formulated from ashless additives to prevent spark-plug fouling and piston ring clogging.

MESRAN MARINE 2T SAE 20 adalah pelumas mesin bensin dua langkah dengan sistem pendinginan air. Pelumas ini diformulasikan dari aditif ashless sehingga mencegah pengotoran busi dan kemacetan cincin torak.

TYPICAL CHARACTERISTICS		
Characteristics	Test Method	MESRAN MARINE 2T SAE 20
SAE Viscosity Grade		20
Density at 15 °C, kg/l	ASTM D - 4052	0.8702
Kinematic Viscosity at 40 °C, cSt at 100 °C, cSt	ASTM D - 445	30.92
Viscosity Index	ASTM D - 445	6.012
Colour	ASTM D - 2270	144
Flash Point (COC), °C	Visual	Green
Pour Point, °C	ASTM D - 92	78
Total Base Number (TBN), mg KOH/g	ASTM D - 5950	-39
	ASTM D - 2896	3.21

PERFORMANCE LEVELS

MESRAN MARINE 2T SAE 20 complies with NMMA TC-W3 requirement.

SUPERIORITIES

- Designed with special detergent technology that provides optimum protection from deposit, excessive wear and rust.
- Ashless lubricant that suitable for outboard engine.

APPLICATIONS

MESRAN MARINE 2T SAE 20 is applied as a lubricant for two stroke gasoline engines with water cooling system such as jetski or motor boat, the latest model of high-powered outboard motor but also very suitable for smaller outboard motor.

TINGKATAN MUTU

MESRAN MARINE 2T SAE 20 memenuhi persyaratan NMMA TC-W3.

KEUNGGULAN

- Didesain dengan teknologi detergent khusus yang memberikan perlindungan optimal bagi mesin dari deposit, keausan berlebih dan karat.
- Pelumas yang tidak mengandung metal detergent sehingga sesuai digunakan pada mesin outboard.

PENGGUNAAN

MESRAN MARINE 2T SAE 20 digunakan sebagai oli samping untuk pelumasan mesin bensin dua langkah dengan sistem pendingin air seperti jetski, motor boat, motor tempel modern yang bertenaga besar dan juga dapat digunakan pada motor tempel yang lebih kecil.