

PRIMA X'TREME SAE 10W-30

PRIMA X'TREME SAE 10W-30 is a high quality gasoline engine oil formulated from balance base oils and selected additives.

PRIMA X'TREME SAE 10W-30 adalah pelumas mesin kendaraan bensin yang diformulasikan dari base oil dan aditif pilihan.

TYPICAL CHARACTERISTICS		
Characteristics	Test Method	PRIMA X'TREME
SAE Viscosity Grade	-	10W-30
Density at 15 °C, kg/l	ASTM D - 4052	0.8788
Kinematic Viscosity at 40 °C, cSt	ASTM D - 7279	68.44
	ASTM D - 7279	10.55
Viscosity Index	ASTM D - 2270	142
	ASTM D - 1500	2.5
ASTM Colour	ASTM D - 1500	2.5
Flash Point, °C	ASTM D - 92	222
Pour Point, °C	ASTM D - 5950	-27
Total Base Number (TBN), mg KOH/g	ASTM D - 2896	6

PERFORMANCE LEVELS

PRIMA X'TREME SAE 10W-30 meets performance level of API SL (approved) and ILSAC GF-3.

TINGKATAN MUTU

PRIMA X'TREME SAE 10W-30 memenuhi tingkatan mutu API SL (*approved*) dan ILSAC GF-3.

SUPERIORITIES

- Good oxidation stability that gives durable performance.
- Provides engine cleanliness and protection from excessive wear.
- Compatible with exhaust emission system technology.

KEUNGGULAN

- Kestabilan oksidasi yang baik sehingga memberikan kinerja yang handal.
- Menjaga kebersihan mesin dan melindungi mesin dari keausan berlebih.
- Cocok dengan teknologi sistem emisi gas buang.

APPLICATIONS

PRIMA X'TREME SAE 10W-30 is recommended for gasoline engine oil that requires above viscosity and performance level.

PENGGUNAAN

PRIMA X'TREME SAE 10W-30 dapat digunakan pada berbagai kendaraan berbahan bakar bensin yang mempersyaratkan kekentalan dan tingkatan mutu di atas.