



MESRANIA 2T SUPER SAE 20

MESRANIA 2T SUPER SAE 20 is a lubricating oil for two stroke gasoline engine with water & air cooling system. This oil is formulated from specific base oils and excellent performance additive to dissolve easily with gasoline and reducing deposit formation, preventing wear and corrosion of engine parts and protecting against spark-plug fouling.

MESRANIA 2T SUPER SAE 20 adalah pelumas mesin bensin dua langkah dengan sistem pendinginan air & udara. Pelumas ini diformulasikan dari base oil dan performance additive terbaik yang mudah larut dalam bahan bakar bensin dan dapat mengurangi timbulnya deposit, mencegah keausan dan karat dari bagian mesin serta memelihara kebersihan busi.

TYPICAL CHARACTERISTICS		
Characteristics	Test Method	MESRANIA 2T SUPER SAE 20
SAE Viscosity Grade		20
Density at 15 °C, kg/L	ASTM D - 4052	0.8770
Kinematic Viscosity at 40 °C, cSt	ASTM D - 445	44.90
at 100 °C, cSt	ASTM D - 445	7.31
Viscosity Index	ASTM D - 2270	126
Colour	Visual	Dark Blue
Flash Point (COC), °C	ASTM D - 92	93
Pour Point, °C	ASTM D - 5950	-39
Sulfated ash, %wt	ASTM D - 874	0.02

PERFORMANCE LEVELS

MESRANIA 2T SUPER SAE 20 complies with TC-W requirement from NMMA (National Marine Manufacturers Association) and JASO FB (Approved).

TINGKATAN MUTU

MESRANIA 2T SUPER SAE 20 memenuhi persyaratan TC-W dari NMMA (National Marine Manufacturers Association) dan JASO FB (Approved).

APPLICATIONS

MESRANIA 2T SUPER SAE 20 is suitable for two stroke gasoline engine with water cooling system such as outboard engines or two stroke air cooled engines such as chainsaw, bajaj, bemo and others.

PENGGUNAAN

MESRANIA 2T SUPER SAE 20 digunakan sebagai oli samping untuk pelumasan mesin bensin dua langkah berpendingin air seperti motor boat atau mesin dua langkah berpendingin udara seperti mesin gergaji, bajaj, bemo dan lainnya.