

PERTAMINA ATF DEXRON®-VI

PERTAMINA ATF DEXRON®-VI is a premium automatic transmission fluid which specially formulated and approved for the latest General Motors Dexron®-VI specification.

TYPICAL CHARACTERISTICS		
Characteristic	Test Method	PERTAMINA ATF DEXRON®-VI
Appearance	-	clear
Density at 15 °C, kg/l	ASTM D - 4052	0.8503
Kinematic Viscosity, at 40 °C, cSt at 100 °C, cSt	ASTM D - 445	30.30
	ASTM D - 445	6.050
Viscosity Index	ASTM D - 2270	151
Colour Visual	Visual	Red
Flash Point, °C	ASTM D - 92	212

PERFORMANCE LEVEL

General Motors Dexron®-VI (approved).

SUPERIORITIES

- Excellent friction stability to provide smooth gear shifting and help to prevent transmission vibration (shudder), thus improving performance of new and older GM transmissions.
- Protects transmission gears against wear and corrosion.
- Provide excellent thermal and oxidation stability.

APPLICATION

PERTAMINA ATF DEXRON®-VI is recommended for automatic transmissions of General Motors vehicles 2006 onwards. Pertamina ATF Dexron®-VI can also be used wherever Dexron®-II and/or Dexron®-III are recommended in GM vehicles and transmissions.

HEALTH AND SAFETY

Please contact our Marketing Head Office to get Material Safety Data Sheet as information for Health and Safety Protection at work.

Phone: 62-21 3190 7190/5. Fax : 62-21 3148884/601

Website: www.pertaminalubricants.com or email: hsse.ptpl@pertamina.com