



## CRB Multi 15W-40 CK-4

Diesel Engine Oil

### Description

Castrol CRB Multi 15W-40 CK-4 is a multipurpose heavy duty diesel engine oil, designed to provide superior protection. Conforming to the strict requirements of PC-11 engine oil technology, it can be used in diesel engines where API CK-4, CJ-4 or below is required. It is engineered to help give long and healthy engine life, giving you peace of mind that your diesel engines are protected in a variety of applications and duty cycles.

### Application

#### MAIN BENEFITS:

Castrol CRB Multi 15W-40 CK-4 is a versatile product which can be used in a wide range of heavy duty and commercial vehicles commercial vehicles. This makes it ideal for use in mixed fleets. Its special formulation helps to keep the engine cleaner, giving more reliable engine protection and thus prolonging engine life across different vehicles.

### Advantages

Castrol CRB Multi 15W-40 CK-4 provides:

- Protection against oil thickening and deposit build up in critical engine parts
- Better shear stability and protection against viscosity loss for reliable engine protection
- Protection from wear and deposits
- Its versatile use makes it ideal for mixed fleets enabling product rationalization for workshops and mixed fleets

### Specifications and Approvals

- API CK-4
- CAT ECF-3
- Cummins CES 20086
- DDC DFS 93K222
- Ford WSS-M2C171-F1
- Mack EOS-4.5
- RVI RLD-4
- Volvo VDS-4.5

## Typical Characteristics

Name	Method	Units	CRB Multi 15W-40
Appearance	Visual	-	Clear & Bright
Total Base Number	ASTM D2896	mg/g KOH	10
Sulfated Ash Content	ASTM D874	% wt.	1.0
Pour Point	ASTM D97	C	-42
Viscosity, Kinematic 100C	ASTM D445	mm <sup>2</sup> /s	15.5
Viscosity, Kinematic 40C	ASTM D445	mm <sup>2</sup> /s	116
Viscosity Index	ASTM D2270	None	140

CRB Multi 15W-40 CK-4

31 Aug 2017

Castrol, the Castrol logo and related marks are trademarks of Castrol Limited, used under licence.

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Material Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. No responsibility is taken by either BP plc or its subsidiaries for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale. You should consult our local representative if you require any further information.

BP Lubricants USA Inc., 1500 Valley Road, Wayne, NJ 07470

Telephone: 1,800.462.0835

[www.castrol.com/us](http://www.castrol.com/us) Email: [contactus@bp.com](mailto:contactus@bp.com)