



Castrol TranSynd

Fully Synthetic Automatic Transmission Fluid

Description

Castrol TranSynd™ is a premium synthetic universal powershift and automatic transmission fluid with TES 295™ and TES 468™ approvals. TranSynd™ is suitable for use in buses and refuse collection vehicles fitted with automatic transmissions and is recommended for all vehicles where Dexron® III or Mercon® ATFs are required.

Advantages

- Excellent thermal and oxidative stability means that the viscosity remains almost constant helping prevent deposits and oil thickening - this extends transmission life and avoids incorrect gear changing
- Excellent transmission cleanliness under all conditions permits extended oil drain and decreased servicing
- Excellent temperature reduction through reduced friction leads to longer oil and component life and permits extended drain and decreased servicing
- Lower power input means fuel savings potential and reduced emissions
- Optimised frictional characteristics gives smoother gear changing at all ambient temperatures and load conditions
- Constant frictional properties improve driving comfort
- Outstanding cold flow properties enables faster oil flow to all critical components (eg torque converter, friction plates, planetary wheels and brake bands) particularly during cold starts
- More responsive and comfortable gear change. Minimises 'shift stock' when changing gear
- Excellent shear stability properties helps retain full transmission performance over whole oil drain period
- Optimal lubrication ensures constant level of comfort during gear changing
- Good extreme pressure (EP) and anti-wear performance gives better transmission component protection leading to longer life
- Very good seal performance helps avoid oil leakages, reducing repair costs
- Free from chlorine and heavy metals for better environmental compatibility - easier waste oil disposal and recyclability

Typical Characteristics

| Name | Method | Units | TranSynd™ |
|------------------------------|------------|--------------------|-----------|
| Density @ 15C, Relative | ASTM D4052 | g/ml | 0.848 |
| Colour | Visual | - | Red |
| Viscosity, Kinematic 40C | ASTM D445 | mm ² /s | 38 |
| Viscosity, Kinematic 100C | ASTM D445 | mm ² /s | 7.4 |
| Viscosity Index | ASTM D2270 | None | 167 |
| Flash Point, COC | ASTM D92 | °C | 235 |
| Viscosity, Brookfield @ -40C | ASTM D2983 | mPa.s (cP) | 8500 |
| Pour Point | ASTM D97 | °C | -63 |

Product Performance Claims

Allison TES 295,
Allison TES 468
MB-Approval 236.91
MB-Approval 238.22
ZF TE-ML 03M, 04D, 14C, 16M, 16S, 20C, 25C
Voith H55.6336.xx

Storage

All packages should be stored under cover. Where outside storage is unavoidable drums should be laid horizontally to avoid the possible ingress of water and damage to drum markings. Products should not be stored above 60°C, exposed to hot sun or freezing conditions.

Castrol TranSynd

31 Jan 2020

Castrol, the Castrol logo and related marks are trademarks of Castrol Limited, used under licence.

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, to the extent that it is permissible by law to exclude warranties and representations, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Material Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. Refer to the MSDS, available from our website for further information. No responsibility is taken by either Castrol NZ, BP plc or its subsidiaries for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale. You should consult our local representative if you require any further information.

Castrol NZ (a business division of BP Oil New Zealand Limited)
Technical Advice Line 0800 10 40 60 Customer Service 0800 CASTROL (227 876)
www.castrol.co.nz www.msds.castrol.co.nz