

Eni i-Base 15W-40



Engine protection

APPLICATIONS

Eni i-Base 15W-40 is an engine lubricant suitable for gasoline and diesel engines that equip passenger cars or light vans operating under the severest conditions involving (for example: motorway driving, taxi service, stop-go service).

CUSTOMER ADVANTAGES

- **Eni i-Base 15W-40** has an extremely high Viscosity Index which keeps it free-flowing when cold and maintains high viscosity when hot.
- Its superior detergent and dispersant properties effectively inhibit the formation of lacquer, varnish, sludge and other deposits, maintaining in a good condition the engine components.
- Its anti-wear properties ensure long life for all moving parts, substantially reducing the need for engine servicing and overhauls.

SPECIFICATIONS AND APPROVALS

- API SM/CF
- VW 501 01, 505 00 quality
- ACEA A3/B4-10
- MB 229.1



Eni i-Base 15W-40



CHARACTERISTICS

Properties	Method	UNIT	Typical
Density at 15°C	ASTM D 4052	kg/m ³	878
Viscosity at 100°C	ASTM D 445	mm ² /s	14.5
Viscosity at 40°C	ASTM D 445	mm ² /s	109
Viscosity Index	ASTM D 2270	-	140
Viscosity at -20°C	ASTM D 5293	mPa·s	6200
Flash point (COC)	ASTM D 92	°C	220
Pour point	ASTM D 97	°C	-27

