

BW COMP-46SE

AIR COMPRESSOR OIL, ISO VG 46

Description **BW COMP-46SE** is a mineral oil-based compressor oil.

Benefits

1. Low Coefficient of friction - Including effective additives.
2. Durableness - Composition of premium base oil.
3. Water separability, Foam characteristic

Typical properties

Items	Spec.	Test method
Appearance	light yellow transparent	Visual
Kin. Viscosity, 40°C, cSt	46	ASTM D0445
Specific gravity, 15/4°C	0.86	ASTM D1298
Viscosity Index	120	ASTM D2270
Flash Point, COC, °C	240	ASTM D0092
Pour Point, °C, Max.	-35	ASTM D0097
Copper Corrosion, 100°C, 3hrs	1A	ASTM D0130
Water Separability, Max.	10	ASTM D1401
Foaming, sq.I, ml, Max.	10/0	ASTM D0892
Foaming, sq.II, ml, Max.	20/0	
Foaming, sq.III, ml, Max.	10/0	

* Above test results are new fluid's typical properties, can be changed by quality improvement.

Application Screw compressors.
Where mineral oil based compressor oil needed.

Term of validity 12 months from the date of manufacture at sealed state, 0 to 40°C.

Safety information Refer to the our MSDS for safety information

The information contained and the recommendations made in this data sheet are based upon data collected and believed by us to be correct. However, no guarantee or warranty of any kind, expressed or implied, is made herein with respect to the merchandise d