

## **BW COMP-68S**

### **COMPRESSOR OIL, ISO VG 68**

**Description**                    **BW COMP-68S** is a mineral oil-based compressor oil.

**Benefits**

1. Low Coefficient of friction - Including effective additives.
2. Durableness - Composition of premium base oil.
3. Water separability, Foam characteristic

**Typical properties**

Items	Spec.	Test method
Appearance	light yellow transparent liquid	Visual
Kin. Viscosity, 40°C, cSt	68	ASTM D445
Viscosity Index	110	ASTM D2270
Flash Point, COC, °C	250	ASTM D92
Pour Point, °C	-15	ASTM D97
Copper Corrosion, 100°C,	1A	ASTM D130
Specific gravity, 15/4°C	0.87	ASTM D1298
Water Separability, min.	10	ASTM D1401
Foaming, sq.1~3, ml	10/0	ASTM D 892

\* Above test results are new fluid's typical properties, can be changed by quality improvement.

**Application**                    Air compressors that mineral oil based air compressor oil is recommended.

**Term of validity**                12 months from the date of manufacture at sealed state, 0 to 40°C.

**Safety information**            Refer to the our MSDS for safety information

The information contained and the recommendations made in this data sheet are based upon data collected and believed by us to be correct. However, no guarantee or warranty of any kind, expressed or implied, is made herein with respect to the merchandise d