



BW CUT EP-703G

Neat cutting, grinding fluid

Description

BW CUT EP-703G is high performance mineral oil-based, included oily

improver and E/P additives, neat cutting fluids for honing processing.

Benefits 1.Include broaching, tapping and gear cutting, can be used wide ranging

cutting process.

2.It has a good lubricity, odor, anti-oxidative ability, chip removing ability.

Typical properties

Items	Properties	Test mothod
Appearance, conc	Light yellow transparent	-
Specific gravity, 15/4℃	0.82	ASTM D1122
Viscosity, 40°C, mm²/s	2.7	ASTM D445
Flash point, COC, ℃	116	ASTM D92
Copper corrosion, 100 °C, 1hr	Max 2	ASTM D130

^{*} Above test results are new fluid's typical properties, can be changed by quality improvement.

Application Ferrous metals : Honing, Lapping process etc.

Using the concentrate as it is.

Term of validity 12 months from the date of manufacture at sealed state, 0 to 40 °C.

Safety information Refer to the our MSDS for safety information

The information contained and the recommendations made in this data sheet are based upon data collected and believed by us to be correct. However, no guarantee or warranty of any kind, expressed or implied, is made herein with respect to the merchandise described and we assume no responsibility for the results or the use there of.

