

BW FINEPUNCH 33

Water insoluble Punching Fluid

Description

BW FINEPUNCH 33 is designed to be suitable for Aluminium fin pressing operations providing high lubricity by using a excellent lubricant additives and friction modifier.

Benefits

1. Lubrication additives reduce the friction.
2. Residual substance is less
3. Improved surface finish and no scratching.
4. Low smell

Typical properties

Items	Results	Test method
Appearance, conc	Colorless transparent liquid	-
Specific gravity, 15/4 °C	0.764	ASTM D1122
Viscosity, 40 °C, mm ² /s	1.38	ASTM D445
Flash point, °C, Tag	56	ASTM D92

* Above test results are new fluid's typical properties, can be changed by quality improvement.

Application

It can be used at fin pressing operations of Aluminium(alloy), heat exchanger parts

Term of validity

12 months from the date of manufacture at sealed state, 0 to 40 °C.

Safety information

Refer to the our MSDS for safety information

1.attention subject (when use)

Keep away from heat and ignition sources.

Keep drum sealed.

Do not allow moisture penetrate into neat type oil.

Storage drums laid and avoid contacting with land.

The information contained and the recommendations made in this data sheet are based upon data collected and believed by us to be correct. However, no guarantee or warranty of any kind, expressed or implied, is made herein with respect to the merchandise described and we assume no responsibility for the results or the use there of.