

**BW FINEPUNCH 50V****Water insoluble Punching Fluid**

**Description** **BW FINEPUNCH 50V** is designed to be suitable for Motor core Punching operations.

**Benefits**

1. Residual substance is less
2. Improved surface finish and no scratching.
3. Low smell

**Typical properties**

Items	Results	Test method
Appearance, conc	Colorless transparent liquid	-
Specific gravity, 15/4 °C	0.770	ASTM D1122
Viscosity, 40 °C, mm <sup>2</sup> /s	1.44	ASTM D445
Flash point, °C, Tag	57	ASTM D92

\* Above test results are new fluid's typical properties, can be changed by quality improvement.

**Application** It can be used at Punching operations of EGI, CR

**Term of validity** 12 months from the date of manufacture at sealed state, 0 to 40 °C.

**Safety information** Refer to the our MSDS for safety information

- 1.attention subject (when use)
  - Keep away from heat and ignition sources.
  - Keep drum sealed.
  - Do not allow moisture penetrate into neat type oil.
  - Storage drums laid and avoid contacting with land.

The information contained and the recommendations made in this data sheet are based upon data collected and believed by us to be correct. However, no guarantee or warranty of any kind, expressed or implied, is made herein with respect to the merchandise described and we assume no responsibility for the results or the use there of.