

BW FINEPUNCH-50YA**Water insoluble Punching Fluid**

Description **BW FINEPUNCH-50YA** is designed to be suitable for Motor core Punching operations providing high lubricity by using a excellent lubricant additives and friction modifier.

Benefits

1. Lubrication additives reduce the friction.
2. Residual substance is less
3. Improved surface finish and no scratching.

Items	Results	Test method
Appearance, conc	Colorless transparent liquid	-
Specific gravity, 15/4 °C	0.772	ASTM D1122
Viscosity, 40 °C, mm ² /s	0.90	ASTM D445
Flash point, °C, Tag	33.5	ASTM D92

* Above test results are new fluid's typical properties, can be changed by quality improvement.

Application It can be used at Punching operations of EGI, CR
Thickness : Thin plate of below 2mm

Term of validity 12 months from the date of manufacture at sealed state, 0 to 40 °C.

Safety information Refer to the our MSDS for safety information

- 1.attention subject (when use)
Keep away from heat and ignition sources.
Keep drum sealed.
Do not allow moisture penetrate into neat type oil.
Storage drums laid and avoid contacting with land.

The information contained and the recommendations made in this data sheet are based upon data collected and believed by us to be correct. However, no guarantee or warranty of any kind, expressed or implied, is made herein with respect to the merchandise described and we assume no responsibility for the results or the use there of.