

# 2X WHITE - 110

Metalworking Fluids WATER-MISCIBLE CUTTING OIL

## Cost-effective general purpose emulsion fluid with excellent biostability

### DESCRIPTION

2X WHITE-110 is emulsion type general purpose cutting/grinding fluid. Designed for machining cast iron, carbon steel and alloy steel, 2X WHITE-110 features outstanding biostability and cost-effectiveness.

#### **FEATURES**

- Excellent biostability that prevents bad odor from microbiological growth
- Excellent characteristics of emulsion stability and anti-foaming
- Anti-rusting feature which prevents rust during operation and of the equipment

#### TYPICAL ROPERTIES

Light brown, Translucent Appearance, concentration

Appearance, 10vol\$ White emulsion

Specific gravity  $(15/4^{\circ}\mathbb{C})$ : 0.95 pH (Room temperature, 10vol%): 10.0

Foaming test (10vol%, ml): Below 1

Corrosion (Steel plate, 10vol%): No color change

- **APPLICATION** Types of material : Cast iron, Carbon steel, Alloy steel
  - Application : Milling, Turning, Drilling etc.
  - Recommended concentration (Brix): Summer 5~10%, Winter 5~8%

\* When diluting, add the oil onto the water and thoroughly mix enough before use.

#### SHELF LIFE

12 Months if stored in a tightly sealed container in a cool and dry area. Normal storage temperatures should be between 0-40°C (32-104°F).

#### SAFETY INFORMATION

Refer to Material Safety Data Sheet for health and safety information.