

Impeller: Brass



JSW 3

Self-priming "JET" pumps


MODEL		POWER		Q m³/h l/min	0	0.6	0.9	1.2	1.5	1.8	2.1	2.4	2.7	3.0	3.6	4.2	4.8	6.0	7.2	8.4	9.6
Single-phase	Three-phase	kW	HP		0	10	15	20	25	30	35	40	45	50	60	70	80	100	120	140	160
JSWm 3CH	JSW 3CH	1.1	1.5	H metres	64	60	55	51	48	45	42.5	40	39	37	34	31					
JSWm 3BH	JSW 3BH	1.5	2		76	70	67	64	61	58	55.5	53	51	49	45	41	39				
–	JSW 3AH	2.2	3		96	90	86	82	79	75	71.5	69	66	64	58	54	50				
JSWm 3CM	JSW 3CM	1.1	1.5		52	50	48	45	44	42	40	38	37	35	32	29	27	23	20		
JSWm 3BM	JSW 3BM	1.5	2		60	58	56	54	52	51	49	47	46	45	42	39	37	33	30		
–	JSW 3AM	2.2	3		74	70	68	67	65	63	61	59	58	56	54	51	49	44	40		
JSWm 3CL	JSW 3CL	1.1	1.5		42	40	39	38	37	36	35	34	33	32	30	28	26	23	20	17	15
JSWm 3BL	JSW 3BL	1.5	2		51	48	46	45	44	43	42	41	40	39	37	35	33	30	27	24	22
–	JSW 3AL	2.2	3		62	60	58	57	56	55	54	53	52	51	49	47	45	42	39	36.5	35

Q = Flowrate H = Total manometric head HS = Suction height
Manometric suction lift up to 9 M (HS)

Tolerance of characteristic curves in compliance with EN ISO 9906 Grade 3.

MODEL		PORTS		kg	
Single-phase	Three-phase	Inlet	Outlet	1~	3~
JSWm 3CH	JSW 3CH	1¼"	1"	24.9	22.9
JSWm 3BH	JSW 3BH			26.1	25.1
–	JSW 3AH			–	26.4
JSWm 3CM	JSW 3CM			24.9	22.9
JSWm 3BM	JSW 3BM			26.1	25.1

MODEL		PORTS		kg	
Single-phase	Three-phase	Inlet	Outlet	1~	3~
–	JSW 3AM	1¼"	1"	–	26.4
JSWm 3CL	JSW 3CL			24.9	22.9
JSWm 3BL	JSW 3BL			26.1	25.1
–	JSW 3AL			–	26.4



Impeller: Noryl GFN2V



JCR

Self-priming "JET" pumps

MODEL		POWER		Q m³/h l/min	0	0.3	0.6	0.9	1.2	1.5	1.8	2.1	2.4	3.0	3.6	4.2	4.8
Single-phase	Three-phase	kW	HP		0	5	10	15	20	25	30	35	40	50	60	70	80
JCRm 1C	–	0.37	0.50	H metres	35	32	27	24	21	19	17	16	15	13			
JCRm 1B	JCR 1B	0.50	0.70		41	36	31	27	24	22	20	19	17	15			
JCRm 1A	JCR 1A	0.60	0.85		47	42	38	34	31	28.5	26	24	22	19			
JCRm 10H	JCR 10H	0.75	1		56	50	45	41	37	33	30	27	25	22			
JCRm 15H	JCR 15H	1.1	1.5		72	67	61	56	51	47	43	40	37	32			
JCRm 10M	JCR 10M	0.75	1		46	44	41	39	37	35	32	30	28	25	22	21	19
JCRm 15M	JCR 15M	1.1	1.5		55	53	50	48	46	43	41	39	37	34	31	29	27

Q = Flowrate H = Total manometric head HS = Suction height
Manometric suction lift up to 9 M (HS)

Tolerance of characteristic curves in compliance with EN ISO 9906 Grade 3.

MODEL		PORTS		kg	
Single-phase	Three-phase	Inlet	Outlet	1~	3~
JCRm 1C	–	1"	1"	5.6	–
JCRm 1B	JCR 1B			6.4	6.3
JCRm 1A	JCR 1A			6.9	6.4
JCRm 10H-M	JCR 10H-M	1¼"	1"	9.4	9.3
JCRm 15H-M	JCR 15H-M			10.5	10.3

Supplierfilterair.com