


4" SUBMERSIBLE MONOBLOCK

SALI 4" Monoblock submerged pump




Impeller: Technopolymer

MODEL Monofase	POWER		Q	0	0.6	1.2	1.8	2.4	3.0	3.6
	kW	HP		m ³ /h	l/min	0	10	20	30	40
SALI@	0.75	1	H metres	61	58	52	44.5	36	26	15

Q= Flow rate H= Total manometric head

Tolerance of characteristic curves in compliance with EN ISO 9906 Grade 3.

MODEL	PORT Outlet	DIMENSIONS mm			kg
		N° STAGES	∅	h	
Single-phase	1"	8	100	586	11



Impeller: Lexan 141-R

4 BLOK 4" Monoblock Submersible pump

MODEL		POWER		Q	0	0.6	1.2	1.8	2.4	3.0	3.6	PORT Outlet	kg	
Single-phase	Three-phase	kW	HP		m ³ /h	l/min	0	10	20	30	40		50	60
4BLOCKm 2/10	4BLOCK 2/10	0.55	0.75	H metres	66	65	60	54	46	35	20	1 1/4"	12.5	19.9
4BLOCKm 2/13	4BLOCK 2/13	0.75	1		86	85	79	71	60	45	26		14.3	13.7
4BLOCKm 2/20	4BLOCK 2/20	1.1	1.5		128	125	118	108	91	70	39		17.8	16.1

MODEL		POWER		Q	0	1.2	1.8	2.4	3.0	3.6	4.2	4.8	5.4	6.0	PORT Outlet	kg	
Single-phase	Three-phase	kW	HP		m ³ /h	l/min	0	20	30	40	50	60	70	80		90	100
4BLOCKm 4/7	4BLOCK 4/7	0.55	0.75	H metres	46	44	42	40	38	35	31.5	27	23	17	1 1/4"	12.1	11.4
4BLOCKm 4/9	4BLOCK 4/9	0.75	1		60	56	54.5	52	49	45	40.5	35	29	23		13.8	13.2
4BLOCKm 4/14	4BLOCK 4/14	1.1	1.5		92	88	85	81	76	70	63	54.5	45	35		17.0	15.1

MODEL		POWER		Q	0	1.5	3.0	4.5	6.0	7.5	9.0	PORT Outlet	kg	
Single-phase	Three-phase	kW	HP		m ³ /h	l/min	0	25	50	75	100		125	150
4BLOCKm 6/4	4BLOCK 6/4	0.55	0.75	H metres	27	26	24	22	19	15	11	1 1/4"	10.7	9.7
4BLOCKm 6/6	4BLOCK 6/6	0.75	1		40	38	36	33	29	24	17		13.3	11.3
4BLOCKm 6/9	4BLOCK 6/9	1.1	1.5		61	58	54	50	44	35	26		16.5	13.9

Q= Flow rate H= Total manometric head

Tolerance of characteristic curves in compliance with EN ISO 9906 App. A.

4" SUBMERSIBLE MONOBLOCK

Supplierfilterair.com