



## JSW 1 Self-priming "JET" pumps

Impeller: Brass

MODEL		POWER		Q	H metres											
Single-phase	Three-phase	kW	HP		m³/h	0	0.3	0.6	0.9	1.2	1.5	1.8	2.1	2.4	2.7	3.0
JSWm 1C	–	0.37	0.50	l/min	<b>0</b>	<b>5</b>	<b>10</b>	<b>15</b>	<b>20</b>	<b>25</b>	<b>30</b>	<b>35</b>	<b>40</b>	<b>45</b>	<b>50</b>	
JSWm 1B	JSW 1B	0.50	0.70	H metres	35	32	27	24	21	19	17	16	15	14	13	
JSWm 1A	JSW 1A	0.60	0.85		41	36	31	27	24	22	20	19	17	16	15	
					47	42	38	34	31	28.5	26	24	22	21.5	19	

Q = Flow rate H = Total manometric head HS = Suction height  
Manometric suction lift up to **9 M (HS)**

Tolerance of characteristic curves in compliance with EN ISO 9906 Grade 3.

MODEL		PORTS		kg	
Single-phase	Three-phase	Inlet	Outlet	1~	3~
JSWm 1C	–			9.2	–
JSWm 1B	JSW 1B	1"	1"	10.0	9.5
JSWm 1A	JSW 1A			10.3	10.1

Impeller: Brass

## JSW 2 Self-priming "JET" pumps

MODEL		POWER		Q	H metres												
Single-phase	Three-phase	kW	HP		m³/h	0	0.3	0.6	0.9	1.2	1.5	1.8	2.4	2.7	3.0	3.6	4.2
JSWm 10H	JSW 10H	0.75	1	l/min	<b>0</b>	<b>5</b>	<b>10</b>	<b>15</b>	<b>20</b>	<b>25</b>	<b>30</b>	<b>40</b>	<b>45</b>	<b>50</b>	<b>60</b>	<b>70</b>	<b>80</b>
JSWm 12H	JSW 12H	0.90	1.25	H metres	56	51	47	44	41	39	36	32	30	28			
JSWm 15H	JSW 15H	1.1	1.5		64	58	54	51	48	45	43	38	36	34			
JSWm 10M	JSW 10M	0.75	1		70	66	62	58	54	51	48	43	41	38			
JSWm 12M	JSW 12M	0.90	1.25	46	42	40	38	37	35	33	30	29	27	25	23	21	
JSWm 15M	JSW 15M	1.1	1.5	50	48	46	44	42	41	39	36	35	33	31	29	27	
				55	52	50	48	46	45	43	40	39	37	35	33	40	

Manometric suction lift up to **9 M (HS)**

MODEL		PORTS		kg	
Single-phase	Three-phase	Inlet	Outlet	1~	3~
JSWm 10H	JSW 10H			13.7	13.8
JSWm 12H	JSW 12H	1"	1"	14.7	13.6
JSWm 15H	JSW 15H			15.1	14.8

MODEL		PORTS		kg	
Single-phase	Three-phase	Inlet	Outlet	1~	3~
JSWm 10M	JSW 10M			13.7	13.8
JSWm 12M	JSW 12M	1"	1"	14.7	13.6
JSWm 15M	JSW 15M			15.1	14.8

Supplierfilterair.com