UV // Professional Plus





Powered by MAX

660089-R (D4 Premium)

- Highly featured whole-home UV disinfection system with graphical interface designed for recommended flow rates up to 12 gpm (45 lpm).
- Overall footprint is extremely compact due to advanced lamp/chamber technology.
- Features VIQUA's new LCD controller, displaying lamp life remaining, replacement parts & support contact information, and an audible/visual lamp replacement reminder.

PART NUMBERS	
N. America (NEMA 5-15P)	660089-R (D4 Premium)
EU CEE (CEE 7/7)	660090-R
AUS/NZ (AS 3112)	-
UK (BS 1363)	- \X
DISINFECTION FLOW RATES	Flow rates based on 95% UVT water (70% UVT for NSF 55 certified systems)
16 mJ/cm ²	23 GPM (87 lpm) (5.2 m³/hr)
30 mJ/cm ²	12 GPM (45 lpm) (2.7 m³/hr)
40 mJ/cm²	9 GPM (34 lpm) (2 m³/hr)
SPECIFICATIONS	
Dimensions inch (cm)	20 1/2" x 4" (52 cm x 10 cm)
Shipping Weight lbs (kg)	10 lbs (4.5 kg)
Connection Size	3/4" MNPT
Power Consumption	50W
REPLACEMENT PARTS/OPTIONS	
Lamp/Quartz Sleeve Kit	602810-102
UV Lamp Only	602805
Quartz Sleeve Only	602732
Controller	650733R-001
UV Sensor	