

650694-R (D4)



Powered by


- Highly featured whole-home UV disinfection system designed for recommended flow rates up to 12 gpm (45 lpm).
- Overall footprint is extremely compact due to advanced lamp/chamber technology.
- Audible lamp replacement reminder and countdown timer with digital display.
- Indicator lights show the status of the system components with warnings if maintenance is required.

PART NUMBERS	
N. America (NEMA 5-15P)	650694-R (D4)
EU CEE (CEE 7/7)	650696-R
AUS/NZ (AS 3112)	--
UK (BS 1363)	--
DISINFECTION FLOW RATES	
Flow rates based on 95% UVT water (70% UVT for NSF 55 certified systems)	
16 mJ/cm ²	23 GPM (87 lpm) (5.2 m ³ /hr)
30 mJ/cm ²	12 GPM (45 lpm) (2.7 m ³ /hr)
40 mJ/cm ²	9 GPM (34 lpm) (2 m ³ /hr)
SPECIFICATIONS	
Dimensions Inch (cm)	20 1/2" x 4" (52 cm x 10 cm)
Shipping Weight lbs (kg)	10 lbs (4.5 kg)
Connection Size	3/4" MNPT
Power Consumption	50W
REPLACEMENT PARTS/OPTIONS	
Lamp/Quartz Sleeve Kit	602810-102
UV Lamp Only	602805
Quartz Sleeve Only	602732
Controller	650733R-002
UV Sensor	--