

Specifications	HI96711 Free and Total Chlorine
opecineacions -	Tilbor II i i cc ana i otal cilionnic

-	Range	Chlorine, Free (P1)		Chlorine, Total (P2)		
		0.00 to 5.00 mg/L (p	opm)			
	Resolution	0.01 mg/L from 0.00	10 mg/L above 3.50 mg/L (ppm)			
	Accuracy @ 25°C (77°F)	±0.03 mg/L ±3% of I				
	Light Source	tungsten lamp				
-	Light Detector	silicon photocell with	notocell with narrow band interference filter @ 525 nm			
-	Power Supply	9V battery				
-	Auto-off	after ten minutes of non-use in measurement mode; after one hour of non-use in calibration mode; with last reading reminder				
	Environment	0 to 50°C (32 to 122°F); RH max 95% non-condensing				
-	Dimensions	192 x 104 x 69 mm (7.6 x 4.1 x 2.7")				
	Weight	320g (11.3 oz.)				
	Method	adaptation of the USEPA method 330.5 and Standard Method 4500-Cl G				
Info	Ordering Information Centification Centification	H196711 is supplied with sample cuvettes (2) with caps, 9V battery, instrument quality certificate and instruction manual. AL Check standards and testing reagents sold separately H196711C includes photometer, CAL Check standards, sample cuvettes (2) with caps, 9V battery, scissors, cuvette cleaning cloth, instrument quality certificate, instruction				
		manual and rigid carrying case. Reagents sold separately				
	Reagents and Standards	HI96711	HI96701-11	CAL Check standard cuvettes (free CI)		
			HI93701-01	reagents for 100 tests (free CI)		
			HI93701-03	reagents for 300 tests (free CI)		
			HI96711-11	CAL Check standard cuvettes (total CI)		
			HI93711-01	reagents for 100 tests (total CI)		
			HI93711-03	reagents for 300 tests (total CI)		

HI96711

Chlorine, Free and Total Portable Photometer

- CAL Check™
 - Allows for performance verification and calibration of the meter using NIST traceable standards
- · Auto-shut off
- · Built-in timer
 - Displayoftime remaining before a measurement is taken

The HI96711 portable photometer is for the measurement of free and total chlorine. Hanna's portable photometers feature an advanced optical system; the combination of a special tungsten lamp, a narrow band interference filter, and silicon photodetector ensure accurate photometric readings every time. The Hanna exclusive CAL Check feature utilizes ready-made, NIST traceable standards to verify both meter validation and calibration. The exclusive cuvette locking system ensures that the cuvette is inserted into the measurement cell in the same position every time to maintain a consistent path length.

Significance of Use

As one of the oldest and most common forms of disinfection, chlorine improves water quality by destroying disease-producing microorganisms and by reacting with other organic and inorganic substances. Chlorine levels must be actively monitored to ensure sufficient chlorine is present for disinfection, as well as to control adverse euects such as taste, odor, and potential reactions with organic matter to form harmful disinfection byproducts.



