

(AS-9125)



ANTISCALANT AGENT FOR WATER TREATMENT PURPOSE

DESCRIPTION

AS-9125 is an antiscalant agent formulated for water treatment purpose that has been invented especially to prevent deposition of organic and inorganic particulate and colloids, silica fouling and iron fouling. It has yellow to brown color in a form of liquid.

ADVANTAGES

- Proportioned density in a liquid form.
- Prevents deposition of organic and inorganic particulate and colloids.
- Advanced formula to prevent silica fouling.
- Adequate for prevention against iron fouling

PRECAUTIONARY STATEMENTS

ATTENTION: May lead to eye inflammation. Avert contact with eyes and sensitive skin. Rinse with soap and water after handling and before eating. Take off and wash contaminated clothing before reuse. In case of eye contact, cleanse thoroughly with water for 15 minutes and get medical help if irritation recurs. Rinse skin contact areas with soap and water. If consumed, provide 1-2 glasses of water or milk and cause to happen vomiting by tapping finger into the back of victim's throat. Retrieve medical help. Pay attention to all safety provision shown on the label and in the Material Safety Data Sheet.

ATTRIBUTES

Appearance : Yellowish Brown Liquid
Density (g/mL) : 0.9 - 1.2
pH : < 5.0

DOSAGE

AS-9125 is vary depends on the hardness level. For instance, the optimum dosage is about 3 - 10 ppm.

PACKAGING

AS-9125 Packaged in 25 Kg pail.

HANDLING AND SAFETY

AS-9125 can cause severe damage to eyes and skin. Avoid contact with eyes and skin to prevent serious injury. Please refer to detailed information about product's hazard data sheet. Immediately, seek for medical advice to treat serious injuries caused by inappropriate handling with this product.