

VERTICAL MULTISTAGE CENTRIFUGAL PUMPS MODEL CVL

ALL STAINLESS STEEL
BODY PUMP

Technical Data

Flows, Q	:	maks.110 m ³ /h
Head	:	maks. 309 m
Liquid Temp.	:	-20°C hingga +104°C
Operating Pres.	:	maks. 30bar

Applications

- Industrial Plants
- Washing Systems
- Boiler Feeding System
- Water Treatment Systems
- High Rise Building Boosting Systems



Performace Table

MODEL	Ø PIPA	KW	M ³ /JAM	1	2	3	4	5	6
			L/MIN	17	33	50	67	83	100
CVL 2 - 7	1 ¼ x 1 ¼	0.75	DAYA DORONG (M)	59	52	38			
CVL 2 - 11		1.1		87	74	55			
CVL 2 - 15		1.5		121	105	80			
CVL 2 - 22		2.2		173	153	118			
CVL 3 - 15	1 ¼ x 1 ¼	1.1	DAYA DORONG (M)		83	68	44		
CVL 3 - 19		1.5			104	88	58		
CVL 3 - 23T		2.2			119	99	65		
CVL 3 - 27T		2.2			136	116	82		
CVL 5 - 16T	1 ¼ x 1 ¼	2.2	DAYA DORONG (M)			100	94	85	75
CVL 5 - 29T		4				177	168	157	141