



LIQUID -TIGHT FLEXIBLE METAL CONDUIT - EF-Interlocked.

THE PRODUCT - Standard grade liquid-tight flexible conduit

- Galvanized steel strip, interlocked.
- High flexibility suitable to a wide range of application.
- Water - proof
- PVC jacket in grey and black color.

APPLICATION

Seals out abrasives, alcohol, fumes, gases, dirt, oils, water and spray suitable for the following potentials:

- Machine tools
- Air conditioning and ventilation
- Silo and plant
- Computer
- High rise buildings
- Security

Nominal size	Inner diameter		Outside diameter		P.V.C. Jacket thickness		Min. Bending Radius mm.	Length of Each Rol	
	min. mm.	max. mm.	min. mm.	max. mm.	min. mm.	max. mm.		ft.	m.
1/2"	15.70	16.30	20.80	21.30	1.00	1.35	70	100	30
3/4"	20.70	21.30	26.20	26.70	1.10	1.55	100	100	30
1"	26.20	26.90	32.70	33.40	1.70	1.95	150	100	30
1-1/4"	35.10	35.70	41.50	42.20	1.25	1.70	180	50	15
1-1/2"	40.20	40.80	47.40	48.30	1.80	2.30	250	50	15
2"	51.00	51.80	59.40	60.30	2.40	2.80	430	50	15
2-1/2"	62.50	64.00	72.10	73.00	2.00	2.50	550	30	10
3"	77.60	78.80	87.70	88.90	2.50	3.20	800	30	10
4"	101.10	102.50	113.20	114.30	2.80	3.03	1200	30	10

The above data might be changed without prior notice. Special sizes are available on request.

