



Quick Repair Solution for Damaged Conveyor Belting

JACKS Solid Plate Fasteners are designed for heavy-duty work, offering professionals a quick repair solution for their conveyor belts. They are available in a range of sizes, for belt thickness from 5mm to over 21mm.

Key Advantages



Save Time

Quick and Easy Installation for Time Critical Repairs



Save Money

Maximizing Output with Minimal Downtime



Safety

Safe to Install since No Exposure to Chemical or Heat



Other Features

- ✓ No Skills Required for Installation
- ✓ High Impact and Abrasion Resistance
- ✓ No Expensive Installation Tools Required
- ✓ Suitable for Joining Conveyor Belts

Contents


Each box contains 25 fastener set, in which each set consists of;

- Top Plate;
- Bottom Plate with 2 Bolts;
- 2 Nuts

Selection Guide

Fastener Size	Belt Thickness (mm)	For Belts with Mechanical Fastener Ratings Up To (kN/m):	Minimum Pulley Diameter (mm)
1	5 - 11	30	300
190	8 - 14	65	460
1½	11 - 17	50	460
2	14 - 21	75	760

Common Market Applications



Application



Fasteners Sets Required in a Complete Joint

Belt Width (mm)	Fastener Size 1 & 190		Fastener Size 1½ & 2	
	90°	45°	90°	45°
300	9	12	8	10
450	14	19	11	15
600	19	26	15	21
750	24	33	19	27
900	29	40	23	32
1000	32	45	26	36
1050	34	47	27	38
1200	39	54	31	43
1350	44	61	35	49
1500	49	68	39	55
1800	59	82	49	65

NOTE: Required fastener sets may vary from those listed depending on exact fastener size