

## Flowcoat HS



### Standard Colour Chart

	
Ivory	Yellow
	
Light Blue	Dark Blue
	
Light Green	Dark Green
	
Brick Red	Light Grey
	
Steel Grey	Charcoal

The applied colours may differ slightly from the examples shown above.  
Contact our customer services for a true colour sample or a special colour match.

### Description

Flowcoat HS is a solvent free, durable, high performance epoxy resin coating system.

### Typical Uses

Flowcoat HS may be used as a hard wearing coloured floor coating in areas such as factories, warehouses, plants and storerooms.

### Benefits

- Good chemical resistant
- Hard wearing
- Abrasion resistant
- Solvent free, low odour
- Aesthetically attractive - brightens up dull factories and warehouses
- Seamless and hygienic finish
- Low maintenance

### Project References

HK Trade Development Council, KLIA, Snow Jelly Factory, New StraitTimes Newspaper Factory, Erison Mobile Communications, Glaxo Pharmaceutical China.

### System Design



## Model Specification

Product: Flowcoat HS

Finish: Gloss

Thickness: Dependant on specification

Preparatory work and application in accordance with manufacturer's instructions.

## Substrate Requirements

Concrete or screed substrate should be a minimum of 25N/ mm<sup>2</sup>, free from laitance, dust and other contamination. The substrate should be dry to 75% RH as per BS8204 and free from rising damp and ground water pressure.

## Products Included in this System

Flowcoat HS

For actual coverage rates, refer to the appropriate project specification.

Detailed application instructions are available upon request.

## Installation Service

The installation should be carried out by a Flowcrete approved applicator with a documented quality assurance scheme. Obtain details of our approved contractors by contacting our customer service team or enquiring via our web site at [www.flowcreteasia.com](http://www.flowcreteasia.com)

## Environmental Considerations

The finished system is assessed as non-hazardous to health and the environment. The long service life and seamless surface reduce the need for repairs, maintenance and cleaning. Environmental and health considerations are controlled during manufacture and application of the products by Flowcrete staff and fully trained and experienced contractors.

## Aftercare - Cleaning and Maintenance

Clean regularly using a single or double headed rotary scrubber drier in conjunction with a mildly alkaline detergent.

## Important Note

Flowcrete's products are guaranteed against defective materials and manufacture and are sold subject to its standard Terms and Conditions of Sale, copies of which can be obtained on request.

## Technical Information

The figures that follow are typical properties achieved in laboratory tests at 20 °C and at 50% Relative Humidity.

Fire Resistance BS476-7:  
Surface spread of flame: Class1

Slip Resistance TRRL Pendulum Slip Test  
Dry >40, Wet depends on specification

Textured systems are recommended to meet slip resistance value requirements for wet conditions and/or surface contaminants (wet or dry) - please contact our Technical Advisors for further details and specifications.

Thermal Resistance Tolerant up to 60 °C

Water Permeability Nil – Karsten test (impermeable)

Surface Hardness 180secs. Koenig Hardness Test

Chemical Resistance Contact Technical Department

Abrasion Resistance Taber Abrader:  
80 mg loss per 1000 cycles  
(1 kg load using CS10 wheels)

Compressive Strength 60 N/mm<sup>2</sup> (BS6319)

Flexural Strength 60 N/mm<sup>2</sup> (BS6319)

Tensile Strength 15 N/mm<sup>2</sup> (BS6319)

Bond Strength Greater than cohesive strength of 25 N/mm<sup>2</sup> concrete. >1.5 MPa.

## Speed of Cure

	10°C	20°C	30°C
Light traffic	48 hrs	16 hrs	12 hrs
Full traffic	72 hrs	48 hrs	40 hrs
Full chemical cure	12 days	7days	6days

## Customer Service

For more information regarding this product please contact the manufacturer.

Manufacturer	Customer Service
Flowcrete Asia	+(603) 6277 9575
Flowcrete Hong Kong	+(852) 2795 0478
Flowcrete China	+86 10 8472 1912

## Further Information

To ensure you are specifying a fit for purpose floor for your project please consult our Technical Advisors on the number below or visit our website to register your interest in specifying one of the most durable floors on the market.

Flowcrete Asia Sdn Bhd (366254-X)  
The Flooring Technology Centre  
Lot 37631 & 37632, Jalan 6/37A,  
Taman Bukit Maluri,  
Industrial Area Kepong,  
52100 Kuala Lumpur, Malaysia.  
Tel: +(603) 6277 9575  
Fax: +(603) 6277 4645  
Email: [malaysia@flowcrete.com](mailto:malaysia@flowcrete.com)  
Flowcrete Asia is an RPM company

Flowcrete International (Thailand) Co., Ltd  
55/164, Bann Klang Muang Ladprao  
Ladprao Soi 88 Rd.  
Wangthonglang, Bangkok, 10310.  
Tel: +66 2539 3424  
Fax: +66 2539 3427  
E-mail: [thailand@flowcrete.com](mailto:thailand@flowcrete.com)

PT. Flowcrete Indonesia  
2nd Floor, Suite 203,  
Palma One Building,  
Jl. HR Rasuna Said Kav. X2 No. 4  
Jakarta Selatan 12950, Indonesia.  
Tel: +6221 252 3201  
Fax: +6221 252 0720  
E-mail: [indonesia@flowcrete.com](mailto:indonesia@flowcrete.com)

Flowcrete Vietnam  
Representative Office  
3rd Floor, 130 Nguyen Cong  
Tru Street,  
Nguyen Thai Binh Ward,  
District 1, HCMC, Vietnam  
Tel: +848 3821 6561  
Fax: +848 3821 6501  
E-mail: [vietnam@flowcrete.com](mailto:vietnam@flowcrete.com)

Flowcrete Hong Kong Limited  
Unit 1004, 1010/F, COL Tower  
Wharf T & T Square  
123 Hoi Bun Road Kwun Tong,  
Kowloon Hong Kong  
Tel: +(852) 2795 0478  
Fax: +(852) 2795 4842  
Email: [hongkong@flowcrete.com](mailto:hongkong@flowcrete.com)

Flowcrete China  
B2308 Lead International Building  
No. A2 Zhonghuan South Road  
Wangjing Chaoyang District  
Beijing P R C 100102  
Tel: +86 10 8472 1912  
Fax: +86 10 8472 1942  
Email: [china@flowcrete.com](mailto:china@flowcrete.com)