SAFETY DATA SHEET

Conforms to Regulation (EC) No. 1907/2006 (REACH), Annex II - Europe



Sikadur® 732 Comp. A

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Product name : Sikadur® 732 Comp. A

- 1.2 Relevant identified uses of the substance or mixture and uses advised against
- 1.3 Details of the supplier of the safety data sheet

Manufacturer/Distributor : P.T. Sika Indonesia

JL. Raya Cibinong - Bekasi km 20

Limusnunggal Cileungsi

Bogor, 16820 Indonesia

Telephone no. : +62 21 823 0025 **Fax no.** : +62 21 823 0026

e-mail address of person responsible for this SDS

.

Emergency telephone number : -

1.4 Emergency telephone number

Supplier

Telephone number : -

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Product definition : Mixture

Classification according to Directive 1999/45/EC [DPD]

The product is classified as dangerous according to Directive 1999/45/EC and its amendments.

Classification : Xi; R36/38

R43 N; R51/53

Human health hazards: Irritating to eyes and skin. May cause sensitisation by skin contact.

Environmental hazards: Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic

environment.

See Section 16 for the full text of the R phrases or H statements declared above. See Section 11 for more detailed information on health effects and symptoms.

2.2 Label elements

Hazard symbol or symbols :



Indication of danger

: Irritant, Dangerous for the environment

R36/38- Irritating to eyes and skin.

Risk phrases

R43- May cause sensitisation by skin contact.

R51/53- Toxic to aquatic organisms, may cause long-term adverse effects in the

aquatic environment.

Date of issue : 30.05.2012. MSDS no. : 601020-1 1/11

Sikadur® 732 Comp. A 30.05.2012 2/11

SECTION 2: Hazards identification

: S24- Avoid contact with skin. Safety phrases

S37- Wear suitable gloves.

reaction product: bisphenol A-(epichlorhydrin) epoxy resin (number average **Hazardous ingredients**

molecular weight <= 700)

oxirane, mono[(C12-14-alkyloxy)methyl]derivs

Supplemental label

elements

: Contains epoxy constituents. See information supplied by the manufacturer.

2.3 Other hazards

Other hazards which do not: Not available.

result in classification

SECTION 3: Composition/information on ingredients

Substance/mixture : Mixture

Chemical family/ : Filled and modified epoxy resin

Characteristics

		<u>Classification</u>		Туре
Product/ingredient name Identifiers	%	67/548/EEC	Regulation (EC) No. 1272/2008 [CLP]	
reaction product: bisphenol A-(epichlorhydrin) epoxy resin (number average molecular weight <= 700)	>= 35 - < 50	Xi; R36/38	Skin Irrit. 2, H315	[1]
RRN: 01-2119456619-26 EC: 500-033-5 CAS: 25068-38-6 Index: 603-074-00-8		R43 N; R51/53	Eye Irrit. 2, H319 Skin Sens. 1, H317 Aquatic Chronic 2, H411	
Calcium carbonate EC: 207-439-9 CAS: 471-34-1	>= 5 - < 10	Xi; R36/38	Skin Irrit. 2, H315 Eye Irrit. 2, H319	[1]
oxirane, mono[(C12-14-alkyloxy)methyl]derivs EC: 271-846-8 CAS: 68609-97-2 Index: 603-103-00-4	>= 2.5 - < 5	Xi; R36/38 R43 N; R51/53	Skin Irrit. 2, H315 Skin Sens. 1, H317	[1]
solvent naphtha (petroleum), heavy arom. EC: 265-198-5 CAS: 64742-94-5 Index: 649-424-00-3	>= 2.5 - < 10	Xn; R65 R66, R67 N; R51/53	Asp. Tox. 1, H304	[1]
naphthalene EC: 202-049-5 CAS: 91-20-3 Index: 601-052-00-2	>= 0.25 - < 1	Carc. Cat. 3; R40 Xn; R22 N; R50/53	Acute Tox. 4, H302 Carc. 2, H351 Aquatic Acute 1, H400 Aquatic Chronic 1, H410	[1] [2]
		See section 16 for the full text of the R-phrases declared above	See Section 16 for the full text of the H statements declared above.	

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment, are PBTs or vPvBs or have been assigned a workplace exposure limit and hence require reporting in this section.

- [1] Substance classified with a health or environmental hazard
- [2] Substance with a workplace exposure limit
- [3] Substance meets the criteria for PBT according to Regulation (EC) No. 1907/2006, Annex XIII
- [4] Substance meets the criteria for vPvB according to Regulation (EC) No. 1907/2006, Annex XIII

Occupational exposure limits, if available, are listed in Section 8.

: 30.05.2012. Date of issue **MSDS no.** : 601020-1 2/11

Sikadur® 732 Comp. A 30.05.2012 3/11

SECTION 4: First aid measures

4.1 Description of first aid measures

Eye contact : Immediately flush eyes with plenty of water, occasionally lifting the upper and lower

eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10

minutes. Get medical attention.

Inhalation : Get medical attention if adverse health effects persist or are severe.

Skin contact: Flush contaminated skin with plenty of water. Remove contaminated clothing and

shoes. Wash contaminated clothing thoroughly with water before removing it, or wear gloves. Continue to rinse for at least 10 minutes. Get medical attention if symptoms

occur.

Ingestion : Do not induce vomiting unless directed to do so by medical personnel. Maintain an

open airway. Seek immediate medical attention.

Protection of first-aiders : No action shall be taken involving any personal risk or without suitable training. It may

be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash

contaminated clothing thoroughly with water before removing it, or wear gloves.

4.2 Most important symptoms and effects, both acute and delayed

Potential acute health effects

Eye contact: Irritating to eyes.

Inhalation : No known significant effects or critical hazards.

Skin contact: Irritating to skin. May cause sensitisation by skin contact.

Ingestion: Irritating to mouth, throat and stomach.

Over-exposure signs/symptoms

Eye contact : Adverse symptoms may include the following:

irritation watering redness

Inhalation : No specific data.

Skin contact: Adverse symptoms may include the following:

irritation redness

Ingestion: No specific data.

4.3 Indication of any immediate medical attention and special treatment needed

Notes to physician : Treat symptomatically. Contact poison treatment specialist immediately if large

quantities have been ingested or inhaled.

Specific treatments: No specific treatment.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing

media

: Use an extinguishing agent suitable for the surrounding fire.

Unsuitable extinguishing

media

: None known.

5.2 Special hazards arising from the substance or mixture

Hazards from the substance or mixture

: In a fire or if heated, a pressure increase will occur and the container may burst.

Hazardous thermal decomposition products

: Decomposition products may include the following materials:

carbon dioxide carbon monoxide

halogenated compounds metal oxide/oxides

5.3 Advice for firefighters

Date of issue : 30.05.2012. MSDS no. : 601020-1 3/11

Sikadur® 732 Comp. A 30.05.2012 4/11

SECTION 5: Firefighting measures

Special protective actions for fire-fighters

: Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. This material is toxic to aquatic organisms. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.

Special protective equipment for fire-fighters

: Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. Clothing for fire-fighters (including helmets, protective boots and gloves) conforming to European standard EN 469 will provide a basic level of protection for chemical incidents.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

: No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilt material. Avoid breathing vapour or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.

For emergency responders

: If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also Section 8 for additional information on hygiene measures.

6.2 Environmental precautions

: Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities.

6.3 Methods and materials for containment and cleaning up

Small spill

: Stop leak if without risk. Move containers from spill area. Absorb with an inert material and place in an appropriate waste disposal container.

Large spill

Stop leak if without risk. Move containers from spill area. Prevent entry into sewers, water courses, basements or confined areas. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see section 13).

6.4 Reference to other sections

: See Section 1 for emergency contact information.

See Section 8 for information on appropriate personal protective equipment.

See Section 13 for additional waste treatment information.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Protective measures

: Put on appropriate personal protective equipment (see Section 8). Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Do not get in eyes or on skin or clothing. Do not breathe vapour or mist. Avoid release to the environment. Refer to special instructions/safety data sheet. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous.

Advice on general occupational hygiene

Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

Date of issue : 30.05.2012. MSDS no. : 601020-1 4/11

Sikadur® 732 Comp. A 30.05.2012 5/11

SECTION 7: Handling and storage

7.2 Conditions for safe storage, including any incompatibilities

: Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see section 10) and food and drink. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabelled containers. Use appropriate containment to avoid environmental contamination.

7.3 Specific end use(s)

Recommendations : Not available.

Industrial sector specific : Not available.

solutions

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational exposure limits

Product/ingredient name	Exposure limit values
· ·	EU OEL (Europe, 12/2009). Notes: list of indicative occupational exposure limit values TWA: 50 mg/m³ 8 hour(s). TWA: 10 ppm 8 hour(s).

Recommended monitoring procedures

: If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Reference should be made to European Standard EN 689 for methods for the assessment of exposure by inhalation to chemical agents and national guidance documents for methods for the determination of hazardous substances.

Derived effect levels

No DELs available.

Predicted effect concentrations

No PECs available.

8.2 Exposure controls

Appropriate engineering controls

: Good general ventilation should be sufficient to control worker exposure to airborne contaminants. If this product contains ingredients with exposure limits, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure below any recommended or statutory limits.

Individual protection measures

Hygiene measures

: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period.

Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing.

Eye/face protection

: Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts.

Skin protection

Hand protection

: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Reference number EN 374. Suitable for short time use or protection against splashes: Butyl rubber/nitrile rubber gloves. (0,4 mm), breakthrough time <30 min. Contaminated gloves should be removed. Suitable for permanent exposure: Viton gloves (0.4 mm), breakthrough time >30 min.

Date of issue : 30.05.2012. MSDS no. : 601020-1 5/11

Sikadur® 732 Comp. A 30.05.2012 6/11

SECTION 8: Exposure controls/personal protection

Body protection

: Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. Recommended: Use barrier skin cream.

Other skin protection

: Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Respiratory protection

: Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.

organic vapour filter (Type A)

A1: < 1000 ppm; A2: < 5000 ppm; A3: < 10000 ppm

Environmental exposure controls

: Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance

Physical state Paste. Colour : Grey.

Odour Characteristic. Not available. **Odour threshold**

pН

Melting point/freezing point Initial boiling point and boiling

range

: Not available. : Not available.

Flash point : Closed cup: 170°C

Evaporation rate : Not available. Flammability (solid, gas) Not available. **Burning time** : Not applicable. **Burning rate** Not applicable. Upper/lower flammability or : Not available.

explosive limits

: Not available. Vapour pressure Vapour density : Not available.

~1.4 g/cm³ [20°C (68°F)] Density

Relative density : Not available. Solubility(ies) Not available. Partition coefficient: n-: Not available.

octanol/water

: 370°C

Decomposition temperature Not available. : Not available. Viscosity **Explosive properties** Not available. Oxidising properties : Not available.

9.2 Other information

No additional information.

Auto-ignition temperature

Date of issue : 30.05.2012. **MSDS no.** : 601020-1 6/11

Sikadur® 732 Comp. A 30.05.2012 7/11

SECTION 10: Stability and reactivity

10.1 Reactivity : No specific test data related to reactivity available for this product or its ingredients.

10.2 Chemical stability : The product is stable.

reactions

10.3 Possibility of hazardous: Under normal conditions of storage and use, hazardous reactions will not occur.

10.4 Conditions to avoid : No specific data.

10.5 Incompatible materials : No specific data.

10.6 Hazardous decomposition products : Under normal conditions of storage and use, hazardous decomposition products

should not be produced.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
reaction product: bisphenol A-(epichlorhydrin) epoxy resin (number average molecular weight <= 700)	LD50 Dermal	Rabbit	>20000 mg/kg	-
	LD50 Oral	Rat	>5000 mg/kg	-
Calcium carbonate	LD50 Oral	Rat	6450 mg/kg	-
oxirane, mono[(C12-14-alkyloxy)methyl]derivs	LD50 Oral	Rat	17100 mg/kg	-
naphthalene	LD50 Dermal	Rat	>2500 mg/kg	-
	LD50 Oral	Rat	>490 mg/kg	-

Conclusion/Summary : Not available.

Irritation/Corrosion

Product/ingredient name	Result	Species	Score	Exposure	Observation
reaction product: bisphenol A-(epichlorhydrin) epoxy resin (number average molecular weight <= 700)	Eyes - Mild irritant	Rabbit	-	100 milligrams	-
	Eyes - Moderate irritant	Rabbit	-	24 hours 20 milligrams	-
	Eyes - Severe irritant	Rabbit	-	24 hours 5 milligrams	-
	Skin - Moderate irritant	Rabbit	-	24 hours 500 microliters	-
	Skin - Severe irritant	Rabbit	-	24 hours 2 milligrams	-
Calcium carbonate	Eyes - Severe irritant	Rabbit	-	24 hours 750 Micrograms	-
	Skin - Moderate irritant	Rabbit	-	24 hours 500 milligrams	-
oxirane, mono[(C12-14-alkyloxy)methyl]derivs	Skin - Moderate irritant	Rabbit	-	24 hours 500 microliters	-
solvent naphtha (petroleum), heavy arom.	Skin - Mild irritant	Rabbit	-	24 hours 500 microliters	-
naphthalene	Skin - Mild irritant	Rabbit	-	495 milligrams	-
	Skin - Severe irritant	Rabbit	-	24 hours 0.05 Mililiters	-

Conclusion/Summary : Not available.

Date of issue : 30.05.2012. **MSDS no.** : 601020-1 7/11

Sikadur® 732 Comp. A 30.05.2012 8/11

SECTION 11: Toxicological information

Sensitisation

Conclusion/Summary: Not available.

Mutagenicity

Conclusion/Summary: Not available.

Carcinogenicity

Conclusion/Summary: Not available.

Reproductive toxicity

Conclusion/Summary: Not available.

Teratogenicity

Conclusion/Summary: Not available.

Information on the likely

routes of exposure

: Not available.

Potential acute health effects

Eye contact : Irritating to eyes. **Inhalation** : May cause irritation.

Skin contact: Irritating to skin. May cause sensitisation by skin contact.

Ingestion: Irritating to mouth, throat and stomach.

Symptoms related to the physical, chemical and toxicological characteristics

Eye contact: Adverse symptoms may include the following:

irritation watering redness

Inhalation: No specific data.

Skin contact: Adverse symptoms may include the following:

irritation redness

Ingestion : No specific data.

Delayed and immediate effects and also chronic effects from short and long term exposure

Short term exposure

Potential immediate : Not available.

effects

Potential delayed effects : Not available.

Long term exposure

Potential immediate : Not available.

effects

Potential delayed effects : Not available.

Potential chronic health effects

Not available.

Conclusion/Summary : Not available.

General: Once sensitized, a severe allergic reaction may occur when subsequently exposed to

very low levels.

Carcinogenicity: No known significant effects or critical hazards.

Mutagenicity: No known significant effects or critical hazards.

Teratogenicity: No known significant effects or critical hazards.

Developmental effects: No known significant effects or critical hazards.

Fertility effects: No known significant effects or critical hazards.

No known significant effects or critical hazards.

Other information : Not available.

Date of issue : 30.05.2012. MSDS no. : 601020-1 8/11

Sikadur® 732 Comp. A 30.05.2012 9/11

SECTION 12: Ecological information

12.1 Toxicity

Product/ingredient name	Result	Species	Exposure
naphthalene	Acute EC50 1.96 mg/L Marine water	Daphnia	48 hours
	Acute LC50 0.51 mg/L Marine water	Fish	96 hours

Conclusion/Summary: Not available.

12.2 Persistence and degradability

Conclusion/Summary: Not available.

12.3 Bioaccumulative potential

Product/ingredient name	LogP _{ow}	BCF	Potential
naphthalene	3.3	-	high

12.4 Mobility in soil

Soil/water partition coefficient (Koc)

: Not available.

Mobility

: Not available.

12.5 Results of PBT and vPvB assessment

PBT : Not applicable. vPvB : Not applicable.

12.6 Other adverse effects : No known significant effects or critical hazards.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product

Methods of disposal : The generation of waste should be avoided or minimised wherever possible.

Significant quantities of waste product residues should not be disposed of via the foul sewer but processed in a suitable effluent treatment plant. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any

regional local authority requirements.

Packaging : Completely emptied packagings may be given for recycling. Empty packaging may

still contain hazardous residues. Empty packaging should be removed by a licensed

waste contractor.

SECTION 14: Transport information

	ADR/RID - ADN/ADNR	IMDG	IATA
14.1 UN number	UN3082	UN3082	UN3082
14.2 UN proper shipping name	Environmentally hazardous substance, liquid, n.o.s. Epoxide resin	Environmentally hazardous substance, liquid, n.o.s. Epoxide resin	Environmentally hazardous substance, liquid, n.o.s. Epoxide resin
14.3 Transport hazard class(es)	9	9	9
14.4 Packing group	III	III	III

Date of issue : 30.05.2012. MSDS no. : 601020-1 9/11

Sikadur® 732 Comp. A 30.05.2012 10/11

SECTION 14: Transport information

14.5 Environmental hazards	Р	Р	Р
14.6 Special precautions for user	Not available.	Not available.	Not available.
Additional information	Tunnel code (E)	Emergency schedules (EmS) F-A, S-F	-
Classification code	M6		

14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

: Not available.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

EU Regulation (EC) No. 1907/2006 (REACH)

Annex XIV - List of substances subject to authorisation

Substances of very high concern

None of the components are listed.

Annex XVII - Restrictions

: Not applicable.

on the manufacture, placing on the market and use of certain dangerous substances, mixtures and

articles

VOC content (EU) : VOC (w/w): 0.46%

Other EU regulations

REACH Information: : All substances contained in Sika Products are

- preregistered or registered by our upstream suppliers, and/or

preregistered or registered by Sika, and/or
excluded from the regulation, and/or
exempted from the registration.

Europe inventory : All components are listed or exempted.

Product/ingredient name	Carcinogenic effects	Mutagenic effects	Developmental effects	Fertility effects
naphthalene	Carc. Cat. 3; R40	-	-	-

15.2 Chemical Safety Assessment

: This product contains substances for which Chemical Safety Assessments are still required.

SECTION 16: Other information

Indicates information that has changed from previously issued version.

Abbreviations and acronyms: ATE = Acute Toxicity Estimate

CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No.

1272/2008]

DNEL = Derived No Effect Level

EUH statement = CLP-specific Hazard statement PNEC = Predicted No Effect Concentration RRN = REACH Registration Number

Date of issue : **30.05.2012**. **MSDS no.** : 601020-1 **10/11**

Sikadur® 732 Comp. A 30.05.2012 11/11

SECTION 16: Other information

Full text of abbreviated H statements

: H302 Harmful if swallowed.

H304 May be fatal if swallowed and enters airways.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H319 Causes serious eye irritation.
H351 Suspected of causing cancer.
H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.H411 Toxic to aquatic life with long lasting effects.

Full text of classifications

[CLP/GHS]

: Acute Tox. 4, H302 ACUTE TOXICITY: ORAL - Category 4
Aquatic Acute 1, H400 AQUATIC TOXICITY (ACUTE) - Category 1
Aquatic Chronic 1, H410 AQUATIC TOXICITY (CHRONIC) - Category 1
Aquatic Chronic 2, H411 AQUATIC TOXICITY (CHRONIC) - Category 2

Asp. Tox. 1, H304 ASPIRATION HAZARD - Category 1 Carc. 2, H351 CARCINOGENICITY - Category 2

Eye Irrit. 2, H319 SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 2

Skin Irrit. 2, H315 SKIN CORROSION/IRRITATION - Category 2

Skin Sens. 1, H317 SKIN SENSITIZATION - Category 1

Full text of abbreviated R phrases

: R40- Limited evidence of a carcinogenic effect.

R22- Harmful if swallowed.

R65- Harmful: may cause lung damage if swallowed.

R36/38- Irritating to eyes and skin.

R43- May cause sensitisation by skin contact.

R66- Repeated exposure may cause skin dryness or cracking.

R67- Vapours may cause drowsiness and dizziness.

R50/53- Very toxic to aquatic organisms, may cause long-term adverse effects in the

aquatic environment.

R51/53- Toxic to aquatic organisms, may cause long-term adverse effects in the

aquatic environment.

Full text of classifications

[DSD/DPD]

: Carc. Cat. 3 - Carcinogen category 3

Xn - Harmful Xi - Irritant

N - Dangerous for the environment

History

Date of printing : 30.05.2012.

Date of issue : 30.05.2012.

Date of previous issue : No previous validation.

Notice to reader

The information contained in this Safety Data Sheet corresponds to our level of knowledge at the time of publication. All warranties are excluded. Our most current General Sales Conditions shall apply. Please consult the product data sheet prior to any use and processing.

Date of issue : 30.05.2012. MSDS no. : 601020-1 11/11