

DIGITAL CLAMP METERS AC

DIGITAL CLAMP METERS AC



MODEL 2002PA/2002R

2002R

- Can measure large AC current up to 2000A.
- Peak hold function.
- 55mm-dia large tear drop shaped jaws.

photo : 2002R

	2002 PA	2002R
AC A	400A(0..400A) ±1%rdg±3dgt(50/60Hz) ±2%rdg±5dgt(40Hz~1kHz) 2000A(0..1500A) ±1%rdg±3dgt(50/60Hz) ±3%rdg±3dgt(40Hz~1kHz) 2000A(1500..2000A) ±3.0%rdg(50/60Hz)	400A(0..400A) ±1.5%rdg±3dgt(45..65Hz) ±2.5%rdg±3dgt(40Hz~1kHz) 2000A(0..1500A) ±2%rdg±5dgt(45..65Hz) ±3%rdg±5dgt(40Hz~1kHz) 2000A(1501..2000A) ±4%rdg(50/60Hz)
AC V	40/400/750V ±1%rdg±2dgt(50/60Hz) ±1.5%rdg±3dgt(40Hz~1kHz)	40/400/750V ±1%rdg±2dgt(45..65Hz) ±1.5%rdg±3dgt(40Hz~1kHz)
DC V	40/400/1000V ±1%rdg±2dgt	
Continuity buzzer	buzzer sounds below 50±35Ω	
Ω	400Ω/4k/40k/400kΩ ±1.5%rdg±3dgt	
Conductor size	φ65mm max.	
Frequency response	40Hz~1kHz	
Output	Rec order: DC400mV against AC400A DC200mV against AC2000A	
Applicable standards	IEC 61010-1 CAT. III 600V CAT. II 1000V IEC 61010-031 IEC 61010-2-032 IEC 61326-1	
Power source	F6P(AA)(1.5V) × 2 Continuous measuring time: approx. 60 hours (2002R) Continuous measuring time: approx. 90 hours (2002P) (Sub-power case: approx. 10 minutes)	
Dimensions	247(L) × 105(W) × 49(D)mm	
Weight	470g approx.	
Accessories	7107A(Test leads) 8201(Output plug)9094(Carrying case) F6P(AA) × 2 Instruction manual	
Optional	8008(Multi-tran) 7014(Output cord)	

CE



MODEL 2017

B33

- Tear drop shaped jaws for ease of use in tight places and crowded cable areas.
- Three functions in one unit; AC current, AC voltage and resistance.
- Resistance range provides audible continuity test.
- Frequency response from 40 Hz to 1kHz on AC current and voltage ranges.

	2017
AC A	200/600A ±1.5%rdg±4dgt(50/60Hz)(200A) ±1%rdg±3dgt(50/60Hz)(600A) ±2%rdg±5dgt(45Hz~1kHz)
AC V	200/600V ±1%rdg±2dgt(50/60Hz) ±1.5%rdg±4dgt(45Hz~1kHz)
Ω	200Ω ±1.2%rdg±2dgt
Continuity buzzer	buzzer sounds below 30±20Ω
Conductor size	φ33mm max.
Frequency response	45Hz~1kHz
Applicable standards	IEC 61010-1 CAT. III 600V Pollution degree 2 IEC 61010-031
Power source	6F22(9V) × 1 Continuous measuring time: approx. 200 hours
Dimensions	208(L) × 91(W) × 40(D)mm
Weight	400g approx.
Accessories	7066A(Test leads) 9079(Carrying case) 6F22 × 1 Instruction manual
Optional	8008(Multi-tran)

CE



MODEL 2027

B33

- True RMS reading instrument that permits precise measurements of non-sinusoidal wave form AC current and voltage.
- Three functions in one unit; AC current, AC voltage and resistance.

	2027
AC A	200/600A(True RMS) ±1.5%rdg±4dgt(50/60Hz)(CF<3) ±2%rdg±5dgt(40Hz~1kHz)(Sine wave)
AC V	200/600V(True RMS)(CF<3) ±1.5%rdg±4dgt(50/60Hz) ±2%rdg±5dgt(40Hz~1kHz)
Ω	200Ω ±1.2%rdg±4dgt
Continuity buzzer	buzzer sounds below 30±20Ω
Conductor size	φ33mm max.
Frequency response	40Hz~1kHz
Applicable standards	IEC 61010-1 CAT. III 600V Pollution degree 2 IEC 61010-031
Power source	6F22(9V) × 1 Continuous measuring time: approx. 200 hours
Dimensions	208(L) × 91(W) × 40(D)mm
Weight	400g approx.
Accessories	7066A(Test leads) 9079(Carrying case) 6F22 × 1 Instruction manual
Optional	8008(Multi-tran)

CE

WIJAYAMAS MACHINERY / PT. WIJAYAMAS TEKNINDO
 Telp : 021 2903 2229 / 021 3237 5508

Fax : 021 5695 5778