

## DRY CHEMICAL POWDER



Dipergunakan untuk bahan biasa mudah terbakar, cairan sangat mudah terbakar, gas dikeluarkan dibawah tekanan dan kebakaran di bawah tegangan listrik

SPESIFIKASI										
MODEL	ZF 10 P	ZF 20 P	ZF 30 P	ZF 45 P	ZF 50 P	ZF 60 P	ZF 90 P	ZF 250 P	ZF 500 P	ZF 750 P
WORKING PRESSURE	15 Bar	15 Bar	15 Bar	15 Bar	15 Bar	15 Bar	15 Bar	15 Bar	15 Bar	15 Bar
TEST PRESSURE	27 Bar	27 Bar	27 Bar	27 Bar	27 Bar	27 Bar	27 Bar	27 Bar	27 Bar	27 Bar
DISCHARGE TIME	6 SEC	7 SEC	8 SEC	10 SEC	11 SEC	13 SEC	16 SEC	25 SEC	50 SEC	60 SEC
EXTINGUISHING MEDIUM	1KG ABC POWDER	2KG ABC POWDER	3KG ABC POWDER	4,5KG ABC POWDER	5KG ABC POWDER	6KG ABC POWDER	9KG ABC POWDER	25KG ABC POWDER	50KG ABC POWDER	75KG ABC POWDER
PROPELLANT GAS	NITROGEN									



## CARBON DIOXIDE (CO<sub>2</sub>)



Dipergunakan untuk kebakaran pada minyak, cairan fimmable & gas, alat listrik, alat mekanik peralatan dan lain-lain tahap awal.

SPESIFIKASI							
MODEL	ZF 20 CD	ZF 30 CD	ZF 50 CD	ZF 70 CD	ZF 90 CD	ZF 250 CD	ZF 450 CD
TEST PRESSURE	250KG/CM <sup>2</sup>	250KG/CM <sup>2</sup>	250KG/CM <sup>2</sup>	250KG/CM <sup>2</sup>	250KG/CM <sup>2</sup>	250KG/CM <sup>2</sup>	250KG/CM <sup>2</sup>
DISCHARGE TIME	22 SEC	22 SEC	22 SEC	30 SEC	30 SEC	40 SEC	50 SEC
DISCHARGE JETS	2-4 M	2-4 M	2-5 M	2-5 M	2-5 M	2-6 M	2-6 M
EXTINGUISHING MEDIUM	2KG CARBON DIOXIDE	3KG CARBON DIOXIDE	5KG CARBON DIOXIDE	7KG CARBON DIOXIDE	9KG CARBON DIOXIDE	25KG CARBON DIOXIDE	45KG CARBON DIOXIDE
PROPELLANT GAS	CARBON DIOXIDE						

## AFF FOAM LIQUID



SPESIFIKASI					
MODEL	ZF 90 AF	ZF 90 AF	ZF 300 AF	ZF 600 AF	ZF 900 AF
WORKING PRESSURE	15 Bar	15 Bar	15 Bar	15 Bar	15 Bar
TEST PRESSURE	27 Bar	27 Bar	27 Bar	27 Bar	27 Bar
DISCHARGE TIME	13 SEC	16 SEC	30 SEC	60 SEC	80 SEC
EXTINGUISHING MEDIUM	6LITER AFF-FOAM	6LITER AFF-FOAM	30LITER AFF-FOAM	60LITER AFF-FOAM	90LITER AFF-FOAM
PROPELLANT GAS	NITROGEN				



Dipergunakan untuk kebakaran pada minyak, cairan fimmable & gas, alat, mekanik peralatan dan lain-lain tahap awal