

T&B® Fittings



T&B Catalog Number: 5333
UPC Number: 78621005333
Description: 3/4" Straight steel insulated liquidtight connector

Status: Active

Features

Ability to install quickly with low torque effort

Application

Used where flexible metal raceway is installed in outdoor or indoor locations where exposed to continuous or intermittent moisture.

To positively bond conduit to box or enclosure.

General

Material: Steel
Finish: Electro Zinc Plated with Chromate Coating
Conduit Size (inches): 3/4

Dimension Information

Dimension A (inches): 1 21/32
Dimension B (inches): 1 5/8
Dimension C (inches): 9/16

Accessories & Components

Wiremesh Grips for Liquidtight Fittings: WMG-LT3

Packaging

T&B Inner Pack: 25
Package in Units: 50
T&B Sold in UOM: Each
T&B Weight Per UOM: 25.2 lbs. per 100

Application Support

Product Overview: Available on Website

Certifications

RoHS Compliance: Yes

Certifications



File Nbr:
E 23018

For further technical assistance, please contact us...

Thomas & Betts - USA
 8155 T&B Blvd.
 Memphis, TN 38125
 www.tnb.com

T&B Technical Support
 MS 3B-50
 8155 T&B Blvd.
 Memphis, TN 38125

Hours: 7AM - 6PM CDT
 Monday-Friday
 Phone: (888) 862-3289
 Fax: (901) 252-1321
 Email: techsupport@tnb.com

