



**DOUBLE BELLOW RUBBER FLEXIBLE JOINT
TWINFLEX SCREWED TYPE**

Size : 15mm ~ 50mm
 Material : Synthetic rubber
 Pressure rating : 16bar
 Type : Double bellow, Screwed connection



**DOUBLE BELLOW RUBBER FLEXIBLE JOINT
TWINFLEX FLANGED TYPE**

Size : 20mm ~ 300mm
 Material : Synthetic rubber
 Pressure rating : 20bar (20mm ~ 150mm)
 16bar (200mm ~ 300mm)
 Type : Double bellow, Flanged connection



**SINGLE BELLOW RUBBER FLEXIBLE JOINT
10-FLEX**

Size : 32mm ~ 300mm
 Material : Synthetic rubber
 Pressure rating : 10bar
 Type : Single bellow, Flanged connection



**SINGLE BELLOW RUBBER FLEXIBLE JOINT
TOZENFLEX**

Size : 20mm ~ 400mm
 Material : Synthetic rubber
 Pressure rating : 16bar
 Type : Single bellow, Flanged connection



**SINGLE BELLOW RUBBER FLEXIBLE JOINT
DYNAFLEX**

Size : 32mm ~ 300mm
 Material : Synthetic rubber
 Pressure rating : 14.7bar (32mm ~ 100mm)
 11.8bar (125mm ~ 300mm)
 Type : Single bellow, Flanged connection

The technical data stated are based on our standard specification. For other specification, please contact our sales office.
 Design and specifications are subject to change without prior notice.