

GST-9800

GST-9800P

GST-9800 Plus with 4 input, 6 output, 304 stainless steel cover

Coated steel cover

304 stainless steel cover



High performance digital weighing indicator offering advanced, flexible functions

Selectable display resolution

A high 1/500,000 count internal resolution, and a selectable display resolution delivers precision for the most demanding application.

Divers up to 8 load cell

Load cell excitation voltage of 12 VDC with the capability of driving up to 8 load cell (350 Ω) in parallel.

Standard RS-232 interface

Serial interfaces available to connect computers, printers or external display.

GST-9800PLUS with 4 input set points

The high 40 times/sec sampling speed makes the GST-9800PLUS' s two batching operation modes. Normal or check weighing batching perfect for demanding batch weighing application.

Digital linearization

The GST-9800, GST-9800P and GST-9800PLUS can improve the performance of load cells with poor linearity. The digital linearization function provides compensation for load cells to improve their linearity.

304 stainless steel cover

GST-9800P and GST-9800PLUS install 304 stainless steel case to protect board.

5 cm high red LED display

Hi-low OK comparison function

Full digital front panel calibration set up capacity and accuracy

GST-9800 coated steel cover with wall mount



Options:

- GST-9800Plus** with 6 set point
- GST-9800P** 304 stainless steel cover
- GST-9800** coated steel cover