

MK-Di02 Load bar

Load bar MK-Di02 gives you the tools to improve profitability and efficiency in many weight-based processes across the Farm.



FEATURES

- Plastic housing
- Support regular shutdown, random code decryption function
- Auto networking and auto auto-creating weighing scale system
- Power on, auto zero-setting range, manual zero-setting range can be set separately, zero tracing range can be set
- RS-232 communication interface, multi communication protocol
- Digital load cell SN checking, overload record checking function
- Calibration switch code
- Input password before calibration and adjusting
- Automatic and manual corner-difference adjustment
- Random charging by indicator
- Encryption function is available while load cell and indicator is communicating
- Equipped with EMC protection

TECHNICAL PARAMETERS

• Digital load cell interface	: RS-485, max transmission distance ≤ 75m
• Transmission speed rate	: 19200 bps
• Digital load cell power supply	: DC 12V/750mA
• Digital load cell connection quantity	: 1 ~ 4 pcs
• Digital load cell communication protocol	: MK-SLB-D protocol
• Display	: 6 LED digital tube with 1.2 inch red light, 7 state instruction
• Serial communication interface	: RS-232, 600 ~ 19200 bps optional
• Indicator power supply	: AC : Switch power supply 110V ~ 200V/AC, 50Hz
• Operating temperature	: 0°C ~ 40°C Humidity : ≤ 85% (RH)
• Storage temperature	: 10°C ~ 60°C Storage Humidity : ≤ 95% (RH)

SPECIFICATIONS

Platter size (mm)	Capacity (kg)	Readability (kg)
1000 x 100	500	0.5
1000 x 100	1000	0.5
1000 x 100	2000	1