

MK - Di02



Introduction

MK-Di02 Digital weighing indicator can be used with 1 - 4 SLB-D or digital load cell. It has the function of accumulation and unit switch over and applies to small platform scale, weighbridge and farmers scale

Characteristic and functions:

1. Plastic housing
2. Calibration switch code
3. Allow single weigh, fixed printing format, not support printing record checking
4. Support regular shutdown, random code decryption function
5. Input password before calibration and adjusting
6. Auto networking and auto auto-creating weighing scale system
7. Automatic and manual corner-difference adjustment
8. Power on, auto zero-setting range, manual zero-setting range can be set separately, zero tracing range can be set
9. Random charging by indicator
10. RS232 communication interface, multi communication protocol
11. Encryption function is available while load cell and indicator is communicating
12. Digital load cell SN checking, overload record checking function
13. Equipped with EMC protection

Main Technical Parameters

Digital load cell interface:	RS485, Max transmission distance $\leq 75m$;
Transmission speed rate:	19200 bps;
Digital load cell power supply:	DC 12V/750mA;
Digital load cell connection quantity:	1~4 pcs;
Digital load cell communication protocol:	MK-LUD-P Protocol, MK-SLB-D Protocol
Display:	6 LED digital tube with 1.2 inch red light, 7 state instruction;
Serial communication interface:	RS232, 600~19200bps optional;
Indicator power supply:	AC: Switch power supply 110V~200V/AC, 50Hz;
Operating temperature:	0°C ~ 40°C Humidity: $\leq 85\%$ (RH);
Storage temperature:	-10°C ~ 60°C Storage Humidity: $\leq 95\%$ (RH);