

Cable – ERICORE



- As an integral part of the ERITECH System 3000, the screened, insulated ERITECH® downconductor conveys the lightning discharge current to ground with minimal danger of sideflashing.
- Capacitance (pF/m) 1100
- Characteristic Impedance (ohms) 4.5
- Cross Sectional Area of centre conductor (mmsq) 55
- Electrical Features include:
- ERITECH® System 3000 ERICORE
- Impulse Voltage withstand (250kV)
- Inductance (nH/m) 22
- Resistance (mohms/m) 0.5
- The unique semi-conductive outer sheath allows electrostatic bonding of the building through cable securing saddles.

Part Number	ERICORE
Article Number	701875
Description	ERICORE Cable, Insulated
Conductor Type	ERICORE
Finish	Insulated
Material	Copper
System	System 3000
Weight	2.64 lb
Width	1.41"
UPC	78285664459
UNSPSC	39121621
ETIM	EC000504

WARNING

ERICO products shall be installed and used only as indicated in ERICO's product instruction sheets and training materials. Instruction sheets are available at www.erico.com and from your ERICO customer service representative. Improper installation, misuse, misapplication or other failure to completely follow ERICO's instructions and warnings may cause product malfunction, property damage, serious bodily injury and death.

Copyright © 2015 ERICO International Corporation. All rights reserved.

CADDY, CADWELD, CRITEC, ERICO, ERIFLEX, ERITECH, and LENTON are registered trademarks of ERICO International Corporation.

