

Welcome

to the HID Advantage
Partner Program



Specification :

Typical maximum* read range

ProxCard® II Card - up to 3" (7.6 cm)
ISOProx® II card - up to 2.5" (6.35 cm)
DuoProx® II Card - up to 2.5" (6.35 cm)
Smart ISOProx®/DuoProx® II Cards - up to 2.5" (6.35 cm)
Proximity & MIFARE® Card - up to 2.5" (6.35 cm)
ProxCard Plus® Card - up to 1.0" (2.5 cm)
ProxKey® II Keyfob - up to 1.5" (3.8 cm)
MicroProx® Tag - up to 2" (5.1 cm)

*Depending on local installation conditions.

Dimensions

3.135" x 1.720" x 0.660" (7.96 x 4.37 x 1.68 cm)

Power Supply

5-16 VDC

Linear power supplies are recommended.

Maximum Current Requirements

Current (DC)

Average 30 mA, Peak 75 mA

Operating Temperature

-22° to 150° F (-30° to 65° C)

Operating Humidity

0-95% relative humidity noncondensing

Weight

2.7 oz. (75 gm)

Current Requirements

20mA avg / 75mA peak at 12VDC

Cable Distance

Wiegand or Clock-and-Data interface:

500 feet (150 m)

Recommended cable is ALPHA 1295 (22 AWG) 5 conductor stranded with overall shield or equivalent.

Certifications

Canada/UL 294 Listed

FCC Certification, United States

Canada Certification

EU and CB Scheme Electrical Safety (EN60950 and IEC60950 ITE Electrical Safety)


Fifteen EU Countries under the R&TTE Directive (EN 300 330 - SRD, and ETS 300 683 - EMC)

CE Mark

Australia C-Tick, New Zealand

Taiwan, China

ProxPoint® Plus 6005



| PT ANUGERAH USAHA MANDIRI |

Jl. Ciputat Raya No.20 Pesona Building, 3rd Floor suite 302, Tanah Kusir –Jakarta Selatan,
Telp. 021-7293736 / 7294489