



PT. MITRA TEKNINDO SEJATI

Jakarta

Galeri Niaga Mediterania 1
Jl. Pantai Indah Utara II Blok. X3 No. G8A-8B
Pantai Indah Kapuk - Jakarta Utara
Telp. 021 52393819

Tangerang I

Kawasan Industri Milenium Blok P2 No. 3
Jl. Pemda Tigaraksa, Sukamulya,
Cikupa, Tangerang - Banten
Telp. 021 59645008

Tangerang II

Kawasan Bizlink Citra Raya Blok O 08/20
Jl. Pemda Tigaraksa, Sukamulya
Cikupa, Tangerang - Banten

Bantaeng

Jl. Dusun Mawang, Desa Papanloe,
Pajukukang, Bantaeng Regency
Sulawesi Selatan

Surabaya

Jl. Raya Gilang 8, Gilang, Kec. Taman, Sidoarjo -
Jawa Timur 61257
Telp. 031 99794078

Makassar

Jl. Ir. Sutami, Pertamina (Pengisian Gas Elpiji)
PT. Pergudangan Permata Alam Blok B No. 10
Makassar - Sulawesi Selatan
Telp 04118037636

Samarinda

Jl. Ampera Pergudangan Mangkupalas Bisnis
Center Blok D20 Simpang Pasir
Palaran, Samarinda - Kalimantan Timur

LONKING

Crawler bulldozer

LG230\LG230S\LG230C\LG230R



Main Specifications



Powered by Weichai 12L four-valve engine Superior and low fuel consumption;



The machine has advanced structure, reasonable layout, and easy operation. Power, low fuel consumption, easy use and maintenance, quality Stable and reliable, high performance efficiency.



Use large-capacity fuel tank, the fuel tank volume reaches 580L, Continuous operation time is longer;



The seat is beautiful and easy to carry forward, backward, Up and down adjustment to better meet different driving needs To reduce the fatigue of drivers;



The operating mechanism is designed according to ergonomic principles, and the steering Joystick and throttle stick sideways to increase neutral Switching and reversing alarm for safer driving;



The planetary power shift transmission has three forward gears and Three reverse gears for fast shifting and steering. Centralized control of combined instrument panel, accurate and reliable;

Overall Specifications

Model	LG230 \\Standard BulLGozer)	LG230C \\Coal BulLGozer)	LG230S \\Swamp BulLGozer)	LG230R \\Landfill BulLGozer)	
Engine					
Engine Power	Crawler Power				
Engine Model	WD12G240E206				
Power/Speed	175kW/1800rpm				
Maximum Torque	1100N.m				
Engine Type	water cooled,inline,four—stroke,direct injection				
Specific Fuel Consumption	208g/kwh				
Fuel Capacity	500L				
Engine Displacement	11.596L				
Blade					
Standard Blade Type	Straight Tilt Blade	U Tilt Blade	Straight Tilt Blade	RubbishBlade	
Optional Blade Type		Half U Blade	/	/	
\\Blade WidthxHeight(mm)	3725 × 1240 4365 × 1055 3800 × 1343 3725 × 1374	3800 × 1343 4200 × 1297	4365 × 1285	4365 × 1885	
Blade Capacity(m³)	6.4 4.7 U7.5 U7	U:7.5 9	6.8	12	
Max.Lifting Height(mm)	1350	1210	1330	1330	
Max.Dingging Depth(mm)	540	540	550	550	
Ripper Type(Optional)	\\Three teeth (single tooth)	\\Three teeth (single tooth)	/	/	
Track Parameter					
Track boards(each side)	39	39	45	45	
Track Width (mm)	560	560 (660)	910	910	
Sprocket pitch (mm)	216				
Track Center Length(mm)	2000	2000	2250	2250	
Entrusted Sprocket Number(each side)	2				
Track Roller(each side)	7	7	8	8	
Groud Pressure(Kpa)	75	75 (70)	41	41	
Min.Ground Clerance(mm)	395	460	520	520	
Gradeability (°)	30				
Vehicle Parameters					
Dimensions(mm)	With ripper	7090 × 3725 × 3590	7850 × 3800 × 3590	/	/
Length x width x height	Without ripper	5500 × 3725 × 3590	6260 × 3800 × 3590	6300 × 4365 × 3600	6000 × 4365 × 3600
Vehicle quality (without ripper)(t)	23.5	24	25.7	26	
Water Capacity (L)	79				
Speed forward(km/h)	3.6; 6.5; 11.2				
Reverse speed(km/h)	4.3; 7.7; 13.2				