

中通 12 米柴油通勤车技术参数

ZHONGTONG 12M DIESEL SHUTTLE BUS PROPOSAL

1. 车辆配置 Bus specification

整车参数 Vehicle parameters	最大载客人数 Max. Passenger capacity	90(含司机) 90 (Include driver)
	座椅数量 Seats	1 个司机座椅, 9 个乘客座椅 1 driver seat with 9 passenger seats
	长 (mm) Length	11990
	宽 (mm) Width	2500
	高 (mm) Height	3260
	轴距 (mm) Wheelbase	6000
	前悬/后悬(mm) Front/Rear Overhang	2670/3320
	Approach/Departure Angle 接近角/离去角	≥7.0°/7.0°
	最小转弯半径 (m) Min.turning radius	≤12
	最大爬坡能力 Grade ability	29%
	总质量 (kg) G.V.W	18000
	燃料种类 Fuel type	柴油 Diesel
	最高车速 (km/h)	100
	发动机 Engine	发动机型号 Engine model
额定功率 (kw) Rated power		220
最大扭矩 (N.m) Max. torque		1160
汽缸数-缸径 × 行程 Cylinder No.s - bore × stroke		108×136
排气量 (L) Displacement		7.47
发动机型式 Engine type		直列、六缸、增压、中冷、直喷 Inline, 6 cylinders, turbocharger,inter-cooler,direct injection

底盘 Chassis	变速箱 Gearbox	FAST 手动 6 挡变速箱 FAST Manual 6 gears transmission
	悬架 Suspension	空气悬挂, 前 2 后 4 气囊, 双向液压减震 Air suspension, front 2 and rear 4 air bags, Two-way hydraulic shock absorber
	前桥 Front axle	东风前桥 Dongfeng front axle
	后桥 Rear axle	东风后桥 Dongfeng rear axle
	制动器 Brake type	双回路气制动, 前盘后鼓式制动 Dual circuit air brake, front disc and rear drum brake
	ABS	ABS 制动系统 ABS brake system
	辅助制动 Assistant brake	电涡流缓速器 Eddy current retarder
	方向机 Steering machine	整体式动力转向 Integral power steering
	油箱 Fuel tank	200L
	轮胎 Tyre	无内胎轮胎, 295/80R22.5 钢轮辋 Tubeless tire, steel wheel rim
车身配置 Body	车身结构 Body structure	全承载, 整车电泳; 二级踏步 Monocoque design, whole bus E-coating; Two steps
	车内地板形式 Floor type	PVC 地板, 地板为花纹铝板 PVC floor, aluminum floor
	乘客门 Passenger door	前双内摆乘客门, 中间左右两侧各一个乘客门 Front double inner swing passenger door, rear passenger door on both left and right
	车外后视镜 Rear-view mirror	标配后视镜 Standard rear-view mirror
	全车玻璃 Glass	司机推拉窗; 侧窗最后左右为内嵌推拉, 其余全封闭, 钢化侧窗玻璃; 两片式全景夹胶前风档, 钢化后风档; 带安全锤 Driver sliding window; the last left and right of the side windows are sliding, the rest are fully sealed, tempered side window glass; two-piece panoramic laminated front windshield, tempered rear windshield; with safety hammer
	行李架 Luggage rack	无行李架, 空调内饰 No luggage rack, A/C interior trimming

	座椅 Seats	驾驶座椅：可调驾驶座椅 (前轮罩上方 4 个乘客座椅 最后排 5 人乘客座椅) Driver seat: air adjustable driver seat; 9 pcs Passenger seats:
电器设施 Electric facility	空调 Air conditioner	32000Kcal, 比泽尔压缩机 Bitzer air compressor
	蓄电池/发电机 Battery/Generator	免维护蓄电池 195A.H×2 发电机 150A Free maintenance battery 195A.H×2 Generator 150A
	后视系统 Rear view system	内视镜, 行车记录仪, CCTV 监控系统包 含倒车监视, 带硬盘存储 Inner view mirror, tachograph, CCTV monitor system back-up monitor, with hard disc storage
	灯具 Lighting	前后大灯, 车内贯通顶灯 front and rear headlights, penetrating dome lights inside the bus
其他设施 Other facility		不锈钢扶手、喊话器、驾驶员前+侧遮阳帘、 4 公斤灭火器两个、天窗 (带换气扇)、 三角警示牌、三角吊环(加密布置), 驾驶 员应急开启乘客门, MP3 播放器, 前顶 1 个 22 寸液晶电视 (U 盘播放) Stainless steel handrails, megaphone, driver's front + side sunshades, two 4 kg fire extinguishers, two sunroofs (with ventilation fans), triangle warning signs, automatic fire extinguishing device for engine room, triangle lifting rings, Driver emergency opening of passenger door, MP3 player, 1 unit 22 inches LCD (U disc player)

2、车辆参考照片





