





|                     |                             | 19746   |
|---------------------|-----------------------------|---|
| Specifications      |                             | CDM6240 (Long Reach)  |
| Operating Weight    | Summary                     | Operating weight 24000kg  The operating weight includes the weight of 8500mm boom, 6500mm standard arm, 0.4m³ bucket, 600mm track shoes, lubricating oil, coolant, the full tank and the rest standard configuration units. |
|                     | Ground pressure             | 48 kPa  |
| Bucket Capacity     | Standard                    | 0.4 m³  |
|                     | Option range                | Buckets can be customized according to actual situation.  |
| Engine              | Model                       | Cummins 6BTAA5.9-C (Euro II)  |
|                     | Rated power                 | 133kW (178hp) /2000 rpm   |
|                     | Max. torque                 | 708 N.m/1500 rpm  |
|                     | Displacement                | 5.9 L   |
| Hydraulic System    | Main pump                   | Axial variable piston pump  |
|                     | Max. flow of system         | 217×2 L/min   |
|                     | Max. pressure of Implements | 34.3 MPa  |
|                     | Max. pilot pressure         | 4.9 MPa   |
|                     | Swing motor                 | Piston Type (with safety valve and closed type brake)   |
|                     | Swing speed                 | 7.5 rpm   |
|                     | Travel motor                | Piston Type (with safety valve and closed type brake)   |
|                     | Travel speed                | 3.0/5.1 km/h  |
|                     | Gradeability                | 35°(70%)  |
|                     | Max. traction               | 222 kN  |
|                     | Max. arm digging force      | 55 kN   |
|                     | Max. bucket digging force   | 90 kN   |
| Fluid Capacity      | Fuel tank                   | 350 L   |
|                     | Hydraulic oil tank          | 220 L   |
| Undercarriage       | Standard track shoes width  | 600 mm  |
|                     | No. of track shoes          | 49 (each side)  |
|                     | No. of carrier rollers      | 2 (each side)   |
|                     | No. of track rollers        | 9 (each side)   |
| Electrical System   | System voltage              | 24 V  |
|                     | Battery capacity            | 12 V, 120 Ah×2  |
| Optional Equipments |                             | Working warning lamp and travel warning device 700mm and 800mm width triple grouser shoes Anti-explosion valve Cab protecting nets Long reach working device and standard device are interchangeable.                       |



## Jakarta

Rukan Sedayu Square Blok D/08, Cengkareng, Jakarta Barat - DKI Jakarta.

## Tangerang

Pergudangan Bizlink Citra Raya Blok P5 No. 31 Jl. Pemda Tigaraksa Kel. Sukamulya Kec. Cikupa Kab. Tangerang - Banten.

## Surabaya

Jl. Gunungsari No. 55-59 (gudang B) Surabaya - Jawa Timur.

## Makassar

Ruko Insingnia Blok B No. 17 Jl. Perintis Kemerdekaan KM 15 Kel. Pai Kec. Biringkanaya Kota Makassar - Sulawesi Selatan.



Efficiency Rules the Future



**OPERATING WEIGHT:** 

**ENGINE POWER:** 

133kW (Euro II)

BUCKET CAPACITY:

0.4m<sup>3</sup>

TRAVEL SPEED:

3.0/5.1km/h