



Benefits

- ▶ Operator comfort with ergonomic palm shape
- ▶ Productivity increased with low vibrations level
- ▶ Powerful and ergonomic palm shape for vertical and horizontal applications
- ▶ 3/16" (5 mm): great for surface preparation from body filler to paint primer

Features

- ▶ Non Vacuum (NV) model in Hook & Loop Pad
- ▶ 5" (125 mm) random orbital palm sander
- ▶ 3/16" (5 mm) orbit
- ▶ Powerful 0.3 hp (210 W) motor
- ▶ Soft grip, tear drop design for perfect control
- ▶ Low noise level
- ▶ Shut-off and speed control switch

Technical description		
Part number	6151933510	
Model	CP3510	
Pad diameter	125 mm	5"
Pad type Hook & Loop	yes	
Pad type PSA	no	
Paper size	125 mm	5"
Orbit diameter	5 mm	3/16"
Free speed	12000 rpm	
Power	210 W	0.3 hp
Self vacuum	Self vacuum	
Vacuum	no	
Pad holes number	6	
Height over spindle	105 mm	4.1"
Spindle thread	5/16-24	
Length	160*150*105	6.3*6*4.1
Net weight	0.74 kg	1.3 lb
Noise level	81 db(A)	
Sound Power	88.6 db(A)	
Vibration (ISO-8662-8)	<2.5 m/s²	
Vibration α (ISO-28927-3)	3 m/s²	
Vibration K (ISO-28927-3)	1.3 m/s²	
Average air consumption	3.8 l/s	8 cfm
Average air consumption	227 l/mn	8 cfm
Actual air consumption	7.6 l/s	16 cfm
Actual air consumption	453 l/mn	16 cfm
Free speed air consumption	9.2 l/s	19.5 cfm
Min. hose size	10 mm	3/8"
Air inlet thread size	0.25 "	