

## CP6060 SASAB - The Best Super Industrial 3/4"



### Benefits

- ▶ Best 3/4" impact to loosen big bolts on very demanding industries
- ▶ Operator comfort and control due to great ergonomics even at high torque levels
- ▶ "Constant & progressive" torque thanks to the 2-Jaw clutch
- ▶ Unmatched durability with reliable mechanism & durable housing
- ▶ Designed for Industrial Maintenance and Production applications

### Features

- ▶ Super Industrial 3/4" impact wrench
- ▶ Reliable 2-jaw clutch
- ▶ Aluminum body & steel clutch housing
- ▶ Durable reverse valve & steel trigger
- ▶ Compact 3-part construction & easy maintenance
- ▶ Hole type socket retainer with o-Ring

### Technical description

|                                   |                  |             |
|-----------------------------------|------------------|-------------|
| <b>Part number</b>                | T024059          |             |
| <b>Model</b>                      | CP6060 SASAB     |             |
| <b>Joint type: soft</b>           | Joint type: soft |             |
| <b>Joint type: hard</b>           | Joint type: hard |             |
| <b>Handle type</b>                | Pistol           |             |
| <b>Square drive</b>               | 3/4"             |             |
| <b>Working Torque Range (fwd)</b> | 265-880 Nm       | 195-650     |
| <b>Maximum Torque (fwd)</b>       | 1350 Nm          | 995 ft.lbs  |
| <b>Maximum Torque (reverse)</b>   | 1356 Nm          | 1000 ft.lbs |

|                                  |                       |                      |
|----------------------------------|-----------------------|----------------------|
| <b>Free speed</b>                | 3500 rpm              |                      |
| <b>Blows per minute</b>          | 1000                  |                      |
| <b>Net weight</b>                | 5.3 kg                | <i>11.7 lb</i>       |
| <b>Power/weight ratio</b>        | 255.8 Nm/kg           | <i>85.5 ft.lb/lb</i> |
| <b>Length</b>                    | 220 mm                | <i>8.6"</i>          |
| <b>Side to center</b>            | 37 mm                 | <i>1.46"</i>         |
| <b>Actual air consumption</b>    | 19.8 l/s              | <i>42 cfm</i>        |
| <b>Air inlet thread size</b>     | 0.375 "               |                      |
| <b>Noise level</b>               | 95 db(A)              |                      |
| <b>Sound Power</b>               | 106 db(A)             |                      |
| <b>Vibration (ISO-8662-7)</b>    | 8 m/s <sup>2</sup>    |                      |
| <b>Vibration α (ISO-28927-2)</b> | 14.2 m/s <sup>2</sup> |                      |
| <b>Vibration K (ISO-28927-2)</b> | 4.1 m/s <sup>2</sup>  |                      |
| <b>Socket retainer</b>           | Hole                  |                      |
| <b>Clutch type</b>               | 2-Jaw                 |                      |
| <b>Bolt size</b>                 | M25                   |                      |