



Benefits

- ▶ Ideal for a variety of heavy Industrial Maintenance applications
- ▶ Reliable & powerful oil bath Pinless Rocking Dog clutch
- ▶ Operator comfort with many ergonomic features
- ▶ 3-part construction reducing downtime maintenance

Features

- ▶ 1" Industrial Pistol impact wrench
- ▶ Oil Bath Pinless rocking dog clutch
- ▶ Durable Aluminum body & Rubber protective cover on clutch housing
- ▶ D-type side handle with Rubber grip
- ▶ Dual (hole & ring) type socket retainer
- ▶ Removable hole plate for suspension
- ▶ Metal trigger & reverse knob for longer durability
- ▶ 3-positions regulator & easy reverse

Technical description

Part number	6151590070	
Model	CP6910-P24	
Joint type: soft	yes	
Joint type: hard	yes	
Handle type	Pistol	
Square drive	1"	
Working Torque Range (fwd)	370-1,550 ft.lbs	500-2,100
Maximum Torque (reverse)	1920 ft.lbs	2600 Nm
Free speed	5000 rpm	
Blows per minute	650	
Net weight	22.5 lb	10.2 kg
Power/weight ratio	85.3 ft.lb/lb	254.9 Nm/kg
Length	11.4"	290 mm
Side to center	2.2"	55 mm
Actual air consumption	40.2 cfm	
VST2	37.7	
Air inlet thread size	0.5 "	
Min. hose size	1/2"	13 mm
Noise level	97 db(A)	
Sound Power	108 db(A)	
Vibration (ISO-8662-7)	N/A m/s²	
Vibration α (ISO-28927-2)	8.9 m/s²	
Vibration K (ISO-28927-2)	2.5 m/s²	
Socket retainer	Dual (hole+friction)	
Clutch type	Pinless Rocking Dog - Oil bath	