



Benefits

- ▶ Our strongest and most powerful 1" impact with an extended anvil
- ▶ Operator productivity
- ▶ Convenient reverse valve for ease of use
- ▶ Ideal for high volume tire work on trucks, buses, and heavy equipment

Features

- ▶ 1" impact wrench
- ▶ Rocking dog clutch
- ▶ 4-position power settings throttle for ease of use
- ▶ Convenient reverse valve
- ▶ Plus 7" extended anvil

Technical description		
Part number	T024585	
Model	CP5000	
Handle type	D-Handle Inside Trigger	
Square drive	1"	
Working Torque Range (fwd)	240-2,800 Nm	185-2,065
Maximum Torque (reverse)	3390 Nm	2500 ft.lbs
Free speed	3700 rpm	
Blows per minute	540	
Net weight	16.2 kg	35.71 lb
Power/weight ratio	209.259259259259 Nm/kg	70.008401008121 ft.lb/lb
Length	572 mm	22.5"
Average air consumption	5.6 l/s	11.88 cfm
Actual air consumption	25 l/s	52 cfm
Air inlet thread size	0.5 "	
Min. hose size	13 mm	1/2"
Noise level	103 db(A)	
Sound Power	114 db(A)	
Vibration (ISO-8662-7)	8.9 m/s²	
Vibration α (ISO-28927-2)	8.5 m/s²	
Vibration K (ISO-28927-2)	2.6 m/s²	
Socket retainer	Dual	
Clutch type	Pinless rocking dog	
Box dimensions	680x240x170	