# **Chicago Pneumatic**







- Durable 1" Impact Wrench
- ✓ High Torque



Vehicle Service

People. Passion. Performance.



## Powerful

1920 ft.lbs - 2600 Nm of maximum torque in reverse

#### **DURABLE**

Closed reinforced rocking dog clutch

### Applications

- Heavy vehicle tire changing
- General mechanical works
- Manufacturing equipment maintenance

## **EXCELLENT CONTROL**

Full teasing trigger

#### **USEFUL**

Forward/Reverse regulator with 3 positions power setting in both directions



#### SHOCK ABSORBING

Rubber bumper protecting both applications and tool (included)

#### CONVENIENT

Socket retainer ring combined with hole retainer

#### COMFORT

Angled down exhaust blows air away from the operator

#### **GREAT HANDLING**

Ergonomic handle with variable positions

N	/lodel	Part Number	Impact Mechanism	Anvil	Free Speed	Working Torque		Max Torque		Weight		Length		Avg. Air Con- sumption		Air Cons.@ Load		Sound Pressure	Sound Power	Vibration
				in	RPM	ft.lbs	Nm	ft.lbs	Nm	lbs	kg	in	mm	cfm	l/s	cfm	l/s	dB(A)	dB(A)	m/s²(k)
CI	P7782	894 107 7820	Rocking dog	Short	5160	440- 1850	600 - 2500	2140	2900	22.2	10.1	14.7	370	10	4.8	40.7	19.2	100	111	6.5 (1.6)
СР	7782-6	894 107 7826	Rocking dog	6"	5160	440- 1850	600 - 2500	2140	2900	25.5	11.6	20.4	520	10	4.8	40.7	19.2	100	111	6.5 (1.6)
CP7	782-SP6	894 107 7821	Rocking dog	#5 6"	5160	440- 1850	600 - 2500	2140	2900	25.5	11.6	20.4	520	10	4.8	40.7	19.2	100	111	6.5 (1.6)



Chicago Pneumatic also offers a large range of accessories to optimize your air tools durability and performance:

Check www.cp.com website for more information.





