



**Chicago
Pneumatic**

CP9121CR - Lightweight & easy handling



Benefits

- ▶ General Maintenance Applications
- ▶ Lightweight rugged housing
- ▶ Durability and performance

Features

- ▶ Keyless adjustable protective guard
- ▶ Aluminum alloy housing
- ▶ Helical bevel gear design
- ▶ 5" (125 mm) wheel capacity
- ▶ 3/8"-24 spindle thread
- ▶ 0.8 hp (600 W) governed motor
- ▶ Ergonomic side handle

Technical description		
Part number	6151952121	
Model	CP9121CR	
Spindle thread	3/8-24	
Wheel size	125 mm	5"
Cup wheel Diam.	-	-
Free speed	12000 rpm	
Power	600 W	0.8 hp
Length	240 mm	9.6"
Net weight	2.1 kg	4.62 lb
Front exhaust	Front exhaust	
Noise level	84 db(A)	
Sound Power	95 db(A)	
Vibration (ISO-8662-4)	2.8 m/s ²	
Vibration α (ISO-28927-1)	11.2 m/s ²	
Vibration K (ISO-28927-1)	3.4 m/s ²	
Average air consumption	6 l/s	12.72 cfm
Average air consumption	360 l/mn	12.72 cfm
Actual air consumption	12 l/s	25.44 cfm
Actual air consumption	720 l/mn	25.44 cfm
Free speed air consumption	9.9 l/s	21 cfm
Min. hose size	10 mm	3/8"
Air inlet thread size	1/4	