

## CP6120 PASED - The Best Super Industrial 1-1/2": Compact, Comfortable & Extremely Durable



## **Benefits**

- ▶ Best 1-1/2" impact to loosen very big bolts quickly and smoothly
- Operator comfort and control thanks to great ergonomics even at VERY high torque
- Constant & progressive torque due to the 2-Jaw clutch
- Unmatched durability with Reliable mechanism & durable housing
- Excellent for very demanding industries such as Heavy Industrial Maintenance & Production applications

## **Features**

- ▶ Super Industrial 1-1/2" impact wrench
- Reliable 2-jaw clutch with the highest Blows per Minute
- Full Teasing (inside) trigger with durable reverse
- Durable aluminum body & indestructible steel clutch housing
- Compact 3-part construction & easy maintenance
- Hole type socket retainer with o-Ring
- ▶ 360° adjustable D-type side handle

| Technical description      |                         |                |  |
|----------------------------|-------------------------|----------------|--|
| Part number                | T018841                 |                |  |
| Model                      | CP6120 PASED            |                |  |
| Joint type: soft           | Joint type: soft        |                |  |
| Joint type: hard           | Joint type: hard        |                |  |
| Handle type                | D-Handle Inside Trigger |                |  |
| Square drive               | 1 1/2"                  |                |  |
| Working Torque Range (fwd) | 815-2,710 Nm            | 600-2,000      |  |
| Maximum Torque (fwd)       | 4740 Nm                 | 3500 ft.lbs    |  |
| Maximum Torque (reverse)   | 4740 Nm                 | 3500 ft.lbs    |  |
| Free speed                 | 3000 rpm                |                |  |
| Blows per minute           | 960                     |                |  |
| Net weight                 | 15.4 kg                 | 33.9 lb        |  |
| Power/weight ratio         | 307.8 Nm/kg             | 103.2 ft.lb/lb |  |

| Length                    | 375 mm               | 14.76" |  |
|---------------------------|----------------------|--------|--|
| Side to center            | 54 mm                | 2.13"  |  |
| Actual air consumption    | 28.3 l/s             | 60 cfm |  |
| Air inlet thread size     | 0.5 "                |        |  |
| Noise level               | 102 db(A)            |        |  |
| Sound Power               | 113 db(A)            |        |  |
| Vibration (ISO-8662-7)    | 12.4 m/s²            |        |  |
| Vibration α (ISO-28927-2) | 21 m/s²              |        |  |
| Vibration K (ISO-28927-2) | 6.6 m/s <sup>2</sup> |        |  |
| Socket retainer           | Hole                 |        |  |
| Clutch type               | 2-Jaw                |        |  |
| Bolt size                 | M40                  |        |  |