



Benefits

- ▶ Best 3/4" impact to loosen big bolts on very demanding industries
- ▶ Operator comfort and control due to great ergonomics even at high torque levels
- ▶ "Constant & progressive" torque thanks to the 2-Jaw clutch
- ▶ Unmatched durability with reliable mechanism & durable housing
- ▶ Perfect for Industrial Maintenance and Production applications

Features

- ▶ Super Industrial 3/4" impact wrench
- ▶ Reliable 2-jaw clutch
- ▶ Aluminum body & steel clutch housing
- ▶ Durable reverse valve & steel trigger
- ▶ Compact 3-part construction & easy maintenance
- ▶ Ring type socket retainer with O-ring

Technical description		
Part number	T024058	
Model	CP6060 SASAR	
Joint type: soft	yes	
Joint type: hard	yes	
Handle type	Pistol	
Square drive	3/4"	
Working Torque Range (fwd)	265-880 Nm	195-650
Maximum Torque (fwd)	1350 Nm	995 ft.lbs
Maximum Torque (reverse)	1356 Nm	1000 ft.lbs
Free speed	3500 rpm	
Blows per minute	1000	
Net weight	5.4 kg	11.9 lb
Power/weight ratio	251.1 Nm/kg	84 ft.lb/lb
Length	220 mm	8.6"
Side to center	37 mm	1.46"
Actual air consumption	19.8 l/s	42 cfm
Air inlet thread size	0.375 "	
Noise level	95 db(A)	
Sound Power	106 db(A)	
Vibration (ISO-8662-7)	8 m/s²	
Vibration α (ISO-28927-2)	14.2 m/s²	
Vibration K (ISO-28927-2)	4.1 m/s²	
Socket retainer	Friction ring	
Clutch type	2-jaw clutch	
Bolt size	M25	